



東芝照明器具配光データシート

名称	蛍光灯器具
形名	FHR-4255ONK-PM9

保守率	良	0.73
	中	0.69
	否	0.61



光源	名称	蛍光ランプ
	形名	FHF32EX-N-H
	光束	3520 lm x 2

効率	F	0%
	F	83%
	F	83%
	器具光束	5870 lm

最大取付間隔	
A-A	1.4 H
B-B	1.3 H

備考	
----	--

前面	下面開放
反射面	塗装(白)

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	284	284	284
10°	283	280	281
20°	275	267	272
30°	262	247	254
40°	233	218	231
50°	185	183	192
60°	108	139	139
70°	40	91	63
80°	15	35	18
90°	0	0	0
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井		80				70				50				30		20		0	
	壁	床	70	50	30	10	70	50	30	10	70	50	30	10	50	30	30	10	10	0
室指数	照明率 (x0.01)																			
0.60	52	48	41	39	33	32	51	47	40	38	33	32	39	37	33	32	32	31	28	26
0.80	63	57	51	48	44	42	61	56	50	47	43	42	49	46	42	41	41	41	37	35
1.00	69	62	58	54	50	47	67	61	57	53	49	47	54	52	48	46	47	46	42	40
1.25	76	67	65	60	57	54	73	66	64	59	56	53	61	57	55	52	53	52	48	46
1.50	80	70	70	63	62	58	77	69	68	63	61	58	65	61	59	57	58	56	52	51
2.00	87	76	78	70	71	65	84	74	76	69	70	65	73	67	67	64	65	63	59	58
2.50	91	78	83	74	77	69	88	77	81	73	75	69	77	71	72	68	69	66	63	62
3.00	94	80	87	76	81	73	91	79	85	75	79	72	80	74	76	71	73	69	67	65
4.00	98	83	92	80	87	77	94	82	89	79	85	76	84	77	81	75	77	73	71	69
5.00	100	84	95	82	91	79	96	83	92	81	88	78	87	79	84	77	79	76	73	72
10.00	104	87	102	86	100	85	101	86	98	85	96	84	92	83	90	82	85	80	79	77

