



# 東芝照明器具配光データシート

名称	蛍光灯器具
形名	FHR-42566NK- -PD9

保守率	良	0.69
	中	0.65
	否	0.61



光源	名称	蛍光ランプ
	形名	FHF32EX-N-H
	光束	4950 lm x 2

効率	F	0%
	F	42%
	F	42%
	器具光束	4191 lm

最大取付間隔	
A-A	1.2 H
B-B	1.2 H

備考	
----	--

前面	乳白アクリルカバー
反射面	塗装 (白)

光度 (cd/1000lm)			
$\theta$	A-A	B-B	C-C
0°	159	159	159
10°	156	155	157
20°	147	147	147
30°	131	133	133
40°	111	115	114
50°	87	94	91
60°	59	68	64
70°	31	41	35
80°	4	13	8
90°	0	0	0
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井		80				70				50				30		20	0		
	壁	床	70	50	30	10	70	50	30	10	70	50	30	10	50	30	30	10	10	0
室指数	照明率 (x0.01)																			
0.60	27	25	21	20	17	17	26	24	21	20	17	17	20	19	17	16	17	16	14	14
0.80	32	29	26	25	22	22	31	29	26	24	22	21	25	24	22	21	21	21	19	18
1.00	35	32	30	27	26	24	34	31	29	27	25	24	28	26	25	24	24	23	22	21
1.25	39	34	33	30	29	27	37	34	32	30	29	27	31	29	28	27	27	26	25	24
1.50	41	36	36	32	32	30	39	35	35	32	31	29	33	31	30	29	29	28	27	26
2.00	44	38	40	35	36	33	43	38	39	35	36	33	37	34	34	32	33	32	30	29
2.50	46	40	42	37	39	35	44	39	41	37	38	35	39	36	37	34	35	34	32	31
3.00	48	41	44	39	41	37	46	40	43	38	40	36	41	37	38	36	37	35	34	33
4.00	49	42	47	40	44	39	48	41	45	40	43	39	43	39	41	38	39	37	36	35
5.00	51	43	48	41	46	40	49	42	47	41	45	40	44	40	42	39	40	38	37	36
10.00	53	44	52	43	50	43	51	44	50	43	49	42	47	42	46	42	43	41	40	39

