



東芝照明器具配光データシート

名称	蛍光灯器具
形名	FHD-21300-P N9

保守率	良	0.66
	中	0.63
	否	0.55



光源	名称	コンパクト形蛍光ランプ
	形名	FHT24EX-N
	光束	1800 lm x 1

効率	F	0%
	F	28%
	F	28%
	器具光束	495 lm

最大取付間隔	
A-A	1.0 H
B-B	1.0 H

備考

前面	下面開放
反射面	塗装(白)

θ	φ	光度 (cd/1000lm)		
		A-A	B-B	C-C
0°		206		
10°		194		
20°		173		
30°		117		
40°		58		
50°		32		
60°		20		
70°		12		
80°		5		
90°		0		
100°		0		
110°		0		
120°		0		
130°		0		
140°		0		
150°		0		
160°		0		
170°		0		
180°		0		

反射率 (%)	天井		80						70						50						30		20		0	
	壁	床	70	50	30	70	50	30	70	50	30	50	30	30	10	30	10	30	10	30	10	30	10	10	0	10
室指数		照明率 (x0.01)																								
0.60		21	19	18	17	16	15	21	19	18	17	16	15	17	17	16	15	15	15	14	14					
0.80		24	22	21	20	19	18	24	22	21	20	19	18	20	19	19	18	18	18	17	17					
1.00		26	23	23	21	21	20	25	23	22	21	20	20	22	21	20	19	20	19	18	18					
1.25		27	24	24	22	22	21	27	24	24	22	22	21	23	22	22	21	21	20	20	19					
1.50		28	25	26	23	24	22	28	25	25	23	23	22	24	23	23	22	22	21	20	20					
2.00		30	26	28	25	26	24	29	26	27	24	25	23	26	24	25	23	24	23	22	22					
2.50		31	27	29	26	27	25	30	26	28	25	27	24	27	25	26	24	25	24	23	22					
3.00		32	27	30	26	28	25	31	27	29	26	28	25	28	25	26	25	25	24	24	23					
4.00		33	28	31	27	30	26	32	27	30	27	29	26	29	26	28	26	26	25	25	24					
5.00		33	28	32	27	31	27	32	28	31	27	30	27	29	27	28	26	27	26	25	25					
10.00		35	29	34	28	33	28	33	28	33	28	32	28	31	28	30	27	28	27	26	26					

