




東芝照明器具配光データシート

名 称	蛍光灯器具	良	0.73		
形 名	FR-42201-PM9	中	0.69		
		否	0.61		
光源	名称	蛍光ランプ			
	形名	FHF32EX-N-H			
	光束	3520 lm x 2			
前 面		効 率	F 	14 %	最大取付間隔 A-A 1.5 H B-B 1.3 H
反射面	塗装 (白)		F 	77 %	
			F 	91 %	
		器具光束		6409 lm	備 考

光度 (cd/1000lm)				反射率 (%)	天井	80						70						50						30			20	0
θ \ φ	A-A	B-B	C-C		壁	70		50		30		70		50		30		50		30		30			10	0		
					床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0	
				室指数	照 明 率 (×0.01)																							
0°				0.60	50	46	36	35	28	27	48	44	35	33	27	27	33	31	26	25	24	24	20	17				
10°				0.80	60	54	46	43	37	36	57	52	44	42	36	35	41	39	34	33	32	31	26	24				
20°				1.00	66	60	53	49	43	41	63	57	51	47	42	40	47	44	39	38	37	36	31	28				
30°				1.25	73	65	60	55	50	47	69	63	58	53	49	46	53	50	46	44	42	41	36	33				
40°				1.50	78	69	65	59	56	52	74	66	62	57	54	50	57	54	50	48	47	45	40	37				
50°				2.00	86	75	74	66	65	60	81	72	71	64	63	58	65	60	58	55	54	52	47	43				
60°				2.50	90	78	80	71	72	65	85	75	76	69	69	63	69	64	63	59	59	56	51	47				
70°				3.00	94	80	85	74	77	69	89	78	81	72	74	67	73	67	68	63	62	60	55	51				
80°				4.00	99	84	91	79	84	74	93	81	86	76	80	72	78	72	74	68	67	64	60	56				
90°				5.00	101	86	95	81	89	77	96	83	90	79	85	75	81	74	77	71	71	67	63	59				
100°				10.00	108	90	104	88	100	85	102	87	99	85	95	83	89	80	86	78	78	74	71	66				
110°																												
120°																												
130°																												
140°																												
150°																												
160°																												
170°																												
180°																												

