


東芝照明器具配光データシート

名称	無電極放電ランプ照明器具
形名	HBL-15000(W)-200H

保守率	良	0.74
	中	0.70
	否	0.61



光源	名称	無電極放電ランプ
	形名	ENDURA150W
	光束	12000 lm × 1

効率	F $\frac{1}{2}$	0%
	F $\frac{1}{4}$	64%
	F $\frac{1}{8}$	64%
	器具光束	7679 lm

最大取付間隔	
A-A	1.9 H
B-B	1.4 H

備考	
----	--

前面	
反射面	鏡面処理

光度 (cd/1000lm)			
θ	A-A	B-B	C-C
0°	160	160	160
10°	182	171	179
20°	199	180	199
30°	220	164	222
40°	226	138	217
50°	197	105	209
60°	108	75	132
70°	3	25	16
80°	2	1	2
90°	1	1	1
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井		80		70		50		30		20		0							
	壁	床	70	50	30	70	50	30	50	30	30	10	10	0						
室指数	照明率 (×0.01)																			
0.60	40	37	31	29	25	24	39	36	30	29	25	24	29	28	24	24	24	23	21	19
0.80	48	44	39	37	34	32	47	43	39	37	33	32	37	36	33	32	32	31	28	27
1.00	53	48	45	42	39	37	52	47	44	41	39	37	42	40	38	36	37	36	33	32
1.25	59	52	51	47	45	42	57	51	50	46	45	42	48	45	43	41	42	41	38	37
1.50	62	55	55	50	49	46	60	54	54	49	49	46	51	48	47	45	46	44	42	40
2.00	68	59	62	55	57	52	66	58	60	54	55	51	57	53	53	50	52	50	47	46
2.50	71	61	65	58	61	55	68	60	63	57	59	54	60	56	57	53	55	53	50	49
3.00	73	62	68	60	64	57	70	62	66	59	63	57	63	58	60	56	57	55	53	52
4.00	76	64	72	62	68	60	73	63	70	61	67	59	66	60	63	58	60	57	56	55
5.00	77	65	74	63	71	62	74	64	72	63	69	61	67	61	65	60	62	59	57	56
10.00	80	67	78	66	77	65	77	66	76	65	74	65	71	64	70	63	66	62	61	60

