

# 東芝照明器具配光データシート



名称	蛍光灯器具
形名	FWT-17600-P N9

光源	名称	ネオスリムZスクエア II
	形名	FHW73EN+FHW 103EN
	光束	17500 lm × 1

前面	
反射面	塗装 (白)

保守率	良	0.73
	中	0.69
	否	0.61

効率	F	0%
	F	82%
	F	82%
	器具 光束	14311 lm



最大取付間隔	
A-A	1.3 H
B-B	1.3 H

備考	
----	--

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	253	253	253
10°	251	251	251
20°	244	242	244
30°	229	225	230
40°	206	202	208
50°	175	169	179
60°	133	128	141
70°	84	80	91
80°	34	32	36
90°	0	0	0
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井		80				70				50				30		20		0	
	壁	床	70	50	30	10	70	50	30	10	70	50	30	10	50	30	30	10	10	0
室指数	照明率 (×0.01)																			
0.60	50	46	38	36	31	30	48	45	37	36	30	30	36	35	30	29	29	29	25	24
0.80	60	54	48	45	40	39	58	53	47	44	40	38	45	43	39	38	38	37	33	32
1.00	66	59	54	50	46	44	64	58	53	50	46	44	51	48	45	43	43	42	38	37
1.25	72	64	61	56	53	50	70	63	60	55	53	50	57	54	51	49	50	48	44	42
1.50	77	68	66	60	59	54	74	66	65	59	58	54	62	58	56	53	54	52	48	47
2.00	84	73	75	67	68	62	81	71	73	66	66	61	69	64	64	60	61	59	56	54
2.50	88	76	80	70	73	66	85	74	77	69	72	65	73	68	68	64	66	63	60	58
3.00	91	78	84	73	78	69	87	77	81	72	76	69	77	71	72	67	69	66	63	61
4.00	95	80	89	77	84	74	91	79	86	76	82	73	81	74	77	72	74	70	68	66
5.00	97	82	92	79	88	76	93	81	89	78	85	76	84	76	81	74	77	73	70	69
10.00	102	85	99	84	97	82	98	84	96	83	94	81	90	81	88	80	83	78	77	75

