




東芝照明器具配光データシート

名 称		蛍光灯器具		保守率	良	0.73		θ	
形 名		FHR-42713N-PM9			中	0.69		ϕ	
					否	0.61			
光 源	名称	メロウライン		効 率	F 	0 %		θ	
	形名	FHF32EX-N-H			F 	78 %			
	光束	3520 lm x 2			F 	78 %			
前 面				器具 光束	5525 lm		最大取付間隔		備考
反射面		塗装 (白)			A-A	1.3 H	B-B	1.3 H	

光度 (cd/1000lm)				反射率 (%)	天井		80						70						50						30			20	0						
$\theta \backslash \phi$	A-A	B-B	C-C		壁	床	70			50			30			70			50			30			50			30			30			10	0
					30		10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
室指数					照 明 率 (×0.01)																														
0.60					51	47	40	38	34	32	50	46	39	38	33	32	38	37	33	32	32	32	28	27											
0.80					61	55	50	47	43	41	59	54	49	47	43	41	48	45	42	41	41	40	37	35											
1.00					66	60	56	52	49	47	64	59	55	51	48	46	53	50	47	46	46	45	42	40											
1.25					73	64	63	57	56	52	70	63	61	57	55	52	59	55	53	51	52	50	47	46											
1.50					76	67	67	61	60	56	74	66	66	60	59	56	63	59	58	55	56	54	51	49											
2.00					83	72	75	67	69	63	80	71	73	66	67	62	69	65	65	61	62	60	57	56											
2.50					86	74	79	70	74	66	83	73	77	69	72	66	73	68	69	65	66	64	61	59											
3.00					89	76	83	72	78	69	86	75	80	72	76	69	76	70	72	67	69	66	64	62											
4.00					92	78	87	75	83	73	89	77	85	75	81	72	80	73	77	71	73	70	67	66											
5.00					94	80	90	77	86	75	91	79	87	76	84	74	82	75	79	73	75	72	70	68											
10.00					98	82	96	81	94	80	95	81	93	80	91	79	87	78	85	77	80	76	74	73											

