



東芝照明器具配光データシート

名 称	蛍光灯器具
形 名	FHR-42492NK -PN9

保守率	良	0.73
	中	0.69
	否	0.61



光源	名称	蛍光ランプ
	形名	FHF32EX-N-H
	光束	3520 lm × 2

効 率	F	0 %
	F	77 %
	F	77 %
	器具 光束	5406 lm

最大取付間隔	
A-A	1.4 H
B-B	1.3 H

備考	
----	--

前 面	ガード
反射面	塗装 (白)

光度 (cd/1000lm)				反射率 (%)	天井	80						70						50						30		20	0	
$\theta \backslash \phi$	A-A	B-B	C-C			壁	70		50		30		70		50		30		50		30		30		10	0		
							30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0
室指数				照 明 率 (×0.01)																								
0.60				47	43	36	34	29	28	45	42	35	33	29	28	34	33	28	27	28	27	24	22					
0.80				56	51	45	42	38	36	55	50	44	42	37	36	43	41	37	36	36	35	31	30					
1.00				62	56	51	47	44	41	60	54	50	47	43	41	48	45	42	40	41	40	36	35					
1.25				68	60	58	53	50	47	66	59	56	52	50	47	54	51	48	46	47	45	42	40					
1.50				72	64	62	57	55	51	70	62	61	56	54	51	58	54	52	50	51	49	46	44					
2.00				79	68	70	63	64	58	76	67	68	62	62	57	65	60	60	56	58	55	52	51					
2.50				82	71	75	66	69	62	79	70	73	65	67	61	69	64	64	60	62	59	56	55					
3.00				85	73	79	69	73	65	82	72	76	68	71	65	72	66	68	63	65	62	59	58					
4.00				89	76	84	72	79	69	86	74	81	71	77	69	76	70	73	67	69	66	64	62					
5.00				91	77	87	74	83	72	88	76	84	73	80	71	79	72	76	70	72	68	66	65					
10.00				96	80	93	79	91	77	92	79	90	78	88	76	84	76	83	75	78	73	72	70					

