



東芝照明器具配光データシート

名称	蛍光灯器具
形名	FHT-42387N-PH9

保守率	良	0.73
	中	0.69
	否	0.61



光源	名称	蛍光ランプ
	形名	FHF32EX-N-H
	光束	4950 lm × 2

効率	F	17%
	F	68%
	F	85%
	器具光束	8447 lm

最大取付間隔	
A-A	1.5 H
B-B	1.3 H

備考	
----	--

前面	
反射面	塗装 (白)

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	162	162	162
10°	162	159	160
20°	159	150	154
30°	157	137	148
40°	153	119	139
50°	146	96	125
60°	138	69	109
70°	135	42	97
80°	121	15	89
90°	78	0	52
100°	67	0	43
110°	58	0	39
120°	58	0	40
130°	55	0	30
140°	40	0	16
150°	16	0	4
160°	2	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井		80				70				50				30		20	0		
	壁	床	70	50	30	10	70	50	30	10	70	50	30	10	50	30	30	10		
室指数	照明率 (×0.01)																			
0.60	46	43	34	32	26	25	44	41	32	31	25	25	30	29	24	23	22	21	17	15
0.80	56	50	43	40	34	33	52	48	41	38	33	32	37	36	31	30	28	28	23	21
1.00	61	55	49	45	40	38	58	53	46	43	38	37	42	40	36	34	33	32	27	24
1.25	68	60	55	51	47	44	64	57	53	49	45	42	48	45	41	39	38	37	32	28
1.50	72	63	60	55	51	48	68	61	57	53	49	46	52	48	45	43	41	40	35	32
2.00	79	69	69	61	60	55	74	66	65	59	58	53	59	54	52	50	48	46	41	37
2.50	83	72	74	65	66	59	78	69	70	63	63	57	63	58	57	54	52	50	45	41
3.00	87	74	78	68	71	63	81	71	74	66	67	61	66	61	61	57	55	53	48	44
4.00	91	77	84	72	77	68	85	74	79	70	73	66	71	65	66	61	60	57	53	48
5.00	94	79	87	75	82	71	88	76	82	72	77	69	74	67	70	64	63	60	55	51
10.00	100	83	96	81	92	78	94	80	90	78	87	76	80	73	78	71	70	66	62	57

