


東芝照明器具配光データシート

名 称	蛍光灯器具	良	0.66		θ 
形 名	FHD-11507-P N9	保守率	0.63		
		否	0.55		
光源	名称	コンパクト形蛍光ランプ		最大取付間隔	備考
	形名	FHT16EX-L			
	光束	1200 lm × 1			
前 面				A-A	1.2 H
反射面	白色			B-B	1.2 H
		効 率	F  0 %		
			F  73 %		
			F  73 %		
		器具光束	873 lm		

光度 (cd/1000lm)				反射率 (%)	天井		80						70						50						30		20	0
$\theta \backslash \phi$	A-A	B-B	C-C		壁	70		50		30		70		50		30		50		30		30		10		0		
					床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10
				室指数	照 明 率 (×0.01)																							
0°				0.60	49	45	39	37	33	32	47	44	38	37	33	32	37	36	32	31	32	31	28	27				
10°				0.80	58	52	48	45	42	40	56	51	47	45	42	40	46	44	41	40	40	39	36	35				
20°				1.00	63	56	53	49	47	45	61	55	52	49	46	44	50	48	45	44	44	43	40	39				
30°				1.25	68	60	59	54	53	50	66	59	58	54	52	49	56	52	51	49	49	48	45	44				
40°				1.50	71	63	63	57	57	53	69	62	62	57	56	53	59	55	54	52	53	51	48	47				
50°				2.00	77	67	70	62	64	59	75	66	68	62	63	58	65	60	61	57	59	56	54	52				
60°				2.50	80	69	74	65	69	62	77	68	72	64	67	61	68	63	64	60	62	59	57	56				
70°				3.00	83	71	77	67	72	64	80	70	75	67	70	64	71	65	67	63	64	62	59	58				
80°				4.00	86	73	81	70	77	68	83	72	78	69	75	67	74	68	71	66	68	65	63	61				
90°				5.00	87	74	83	72	80	70	84	73	81	71	78	69	76	69	74	68	70	66	65	63				
100°				10.00	91	76	89	75	87	74	88	75	86	74	84	73	80	73	79	72	74	70	69	67				

