



東芝照明器具配光データシート

名 称		蛍光灯ブラケット		保守率	良	0.74		θ 			
形 名		FB21931NB			中	0.70			ϕ 		
					否	0.62					
光源	名 称	メロウホワイト		効 率	F 	1 %	最大取付間隔 <table><tr><td>A-A</td><td>1.3 H</td></tr><tr><td>B-B</td><td>1.3 H</td></tr></table>	A-A	1.3 H	B-B	1.3 H
	A-A	1.3 H									
	B-B	1.3 H									
形 名	FL20SS・N/18		F 	63 %							
光 束	1170 lm × 1		F 	64 %							
前 面				器具光束	750 lm	備考					
反射面		白色									

光度 (cd/1000lm)				反射率 (%)	天井		80						70						50						30		20	0			
$\theta \backslash \phi$	A-A	B-B	C-C		壁	70			50			30			70			50			30			50		30		30		10	0
						30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10
室指数				照 明 率 (×0.01)																											
0.60				40	36	30	29	25	24	38	36	30	29	25	24	29	28	24	24	24	23	20	19								
0.80				47	43	38	36	32	31	46	42	38	35	32	31	36	34	31	30	30	30	27	26								
1.00				52	47	43	40	37	35	50	46	42	39	37	35	40	38	36	34	35	34	31	29								
1.25				57	51	49	45	43	40	55	50	47	44	42	39	45	43	40	39	39	38	35	34								
1.50				60	53	52	48	46	43	58	52	51	47	46	43	48	45	44	42	42	41	38	37								
2.00				66	57	59	52	53	49	63	56	57	52	52	48	54	50	50	47	48	46	43	42								
2.50				69	59	63	55	58	52	66	58	61	54	56	51	57	53	54	50	51	49	47	45								
3.00				71	61	66	57	61	54	68	60	63	57	59	54	60	55	56	53	54	51	49	48								
4.00				74	63	70	60	66	58	71	62	67	59	64	57	63	58	60	56	57	54	52	51								
5.00				76	64	72	62	69	60	73	63	69	61	67	59	65	59	63	58	59	56	54	53								
10.00				79	66	77	65	75	64	76	65	75	64	73	63	69	63	68	62	64	60	59	57								

