


東芝照明器具配光データシート

名 称	蛍光灯直付器具	良	0.70		θ 0°
形 名	FC38883 (W) B	中	0.66		
		否	0.62		
光源	名 称	メロウZ	効 率	F 	9 %
	形 名	FCL30EX-N/28-Z		F 	44 %
	光 束	2210 lm × 1		F 	53 %
前 面	乳白アクリルカバー	器具光束	1177 lm	最大取付間隔	
反射面	プラスチック(白)			A-A	1.3 H
				B-B	1.3 H
				備考	

光度 (cd/1000lm)				天井	80			70			50			30			20	0
θ	ϕ	A-A	B-B	C-C	反射率 (%)	壁	70	50	30	70	50	30	50	30	30	10	10	0
0°		126			床	30	10	30	10	30	10	30	10	30	10	30	10	0
10°		125			室指数	照 明 率 (×0.01)												
20°		120			0.60	30	28	23	21	18	17	29	27	22	21	17	17	20
30°		111			0.80	36	33	28	27	23	22	34	31	27	26	23	22	25
40°		99			1.00	40	36	32	30	27	26	38	34	31	29	26	25	28
50°		84			1.25	44	39	36	33	31	29	41	37	35	32	30	28	32
60°		67			1.50	46	41	39	36	34	32	44	39	38	35	33	31	34
70°		51			2.00	51	44	45	40	40	36	48	42	42	38	38	35	39
80°		36			2.50	53	46	48	42	43	39	50	44	45	41	41	38	41
90°		24			3.00	55	47	50	44	46	41	52	46	48	43	44	40	43
100°		16			4.00	58	49	54	46	50	44	55	47	51	45	48	43	46
110°		13			5.00	59	50	56	48	53	46	56	48	53	46	50	44	48
120°		13			10.00	63	53	61	51	59	50	59	51	57	50	56	48	52
130°		13																
140°		14																
150°		14																
160°		14																
170°		10																
180°		0																

