

東芝照明器具配光データシート



名 称	蛍光灯器具
形 名	FHD-31507-P D9

光源	名 称	コンパクト形蛍光ランプ
	形 名	FHT32EX-L
	光束	2400 lm × 1

前 面	
反射面	白色

保守率	良	0.66
	中	0.63
	否	0.55

効 率	F 	0 %
	F 	59 %
	F 	59 %
	器具 光束	1406 lm



最大取付間隔	
A-A	1.2 H
B-B	1.2 H

備考	
----	--

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	249	249	249
10°	249	245	248
20°	233	226	231
30°	205	195	201
40°	170	154	162
50°	119	110	121
60°	68	66	71
70°	36	33	37
80°	19	14	23
90°	0	0	0
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井	80						70						50						30			20	0
	壁	70		50		30		70		50		30		50		30		30			10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0		
室指数		照 明 率 (×0.01)																						
0.60		39	36	31	29	26	25	38	35	31	29	26	25	30	29	26	25	25	25	22	21			
0.80		46	42	38	36	33	32	45	41	38	36	33	32	37	35	32	31	32	31	29	28			
1.00		50	45	43	40	38	36	49	44	42	39	37	35	40	38	36	35	35	35	32	31			
1.25		55	48	47	43	42	40	53	48	46	43	42	39	45	42	41	39	39	38	36	35			
1.50		57	51	51	46	46	42	56	50	50	45	45	42	47	44	44	41	42	41	39	37			
2.00		62	54	56	50	52	47	60	53	55	50	51	47	52	48	49	46	47	45	43	42			
2.50		64	56	59	52	55	50	62	55	58	52	54	49	55	51	52	48	50	48	46	45			
3.00		66	57	62	54	58	52	64	56	60	53	57	51	57	52	54	50	52	49	48	47			
4.00		69	58	65	56	62	54	66	58	63	56	60	54	59	54	57	53	54	52	50	49			
5.00		70	59	67	58	64	56	68	59	65	57	62	55	61	56	59	54	56	53	52	51			
10.00		73	61	72	60	70	59	71	60	69	60	68	59	65	58	63	58	60	56	55	54			

