



# 東芝照明器具配光データシート

|     |              |
|-----|--------------|
| 名 称 | 電球形蛍光灯シャンデリア |
| 形 名 | BFC-4054ZEL  |

|     |   |      |
|-----|---|------|
| 保守率 | 良 | 0.74 |
|     | 中 | 0.70 |
|     | 否 | 0.62 |



|    |     |               |
|----|-----|---------------|
| 光源 | 名 称 | ネオボールZ        |
|    | 形 名 | EFG25EL/20-ZJ |
|    | 光束  | 1370 lm × 4   |

|     |      |         |
|-----|------|---------|
| 効 率 | F    | 19%     |
|     | F    | 32%     |
|     | F    | 51%     |
|     | 器具光束 | 2819 lm |

| 最大取付間隔 |       |
|--------|-------|
| A-A    | 1.4 H |
| B-B    | 1.4 H |

|    |  |
|----|--|
| 備考 |  |
|----|--|

|     |  |
|-----|--|
| 前 面 |  |
| 反射面 |  |

| 光度 (cd/1000lm) |     |     |     |
|----------------|-----|-----|-----|
| θ \ φ          | A-A | B-B | C-C |
| 0°             | 72  |     |     |
| 10°            | 72  |     |     |
| 20°            | 73  |     |     |
| 30°            | 72  |     |     |
| 40°            | 65  |     |     |
| 50°            | 58  |     |     |
| 60°            | 52  |     |     |
| 70°            | 45  |     |     |
| 80°            | 31  |     |     |
| 90°            | 25  |     |     |
| 100°           | 30  |     |     |
| 110°           | 37  |     |     |
| 120°           | 37  |     |     |
| 130°           | 34  |     |     |
| 140°           | 29  |     |     |
| 150°           | 25  |     |     |
| 160°           | 22  |     |     |
| 170°           | 22  |     |     |
| 180°           | 21  |     |     |

| 反射率<br>(%) | 天井 | 80                 |    |    |    |    |    | 70 |    |    |    |    |    | 50 |    |    |    |    |    | 30 |    |   | 20 | 0 |
|------------|----|--------------------|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|---|----|---|
|            | 壁  | 70                 |    | 50 |    | 30 |    | 70 |    | 50 |    | 30 |    | 50 |    | 30 |    | 30 |    |    | 10 | 0 |    |   |
|            | 床  | 30                 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 10 | 0  |   |    |   |
| 室指数        |    | 照 明 率      (×0.01) |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |   |    |   |
| 0.60       |    | 27                 | 25 | 20 | 19 | 15 | 15 | 25 | 23 | 19 | 18 | 15 | 14 | 16 | 15 | 13 | 13 | 11 | 11 | 9  | 7  |   |    |   |
| 0.80       |    | 32                 | 29 | 25 | 23 | 20 | 19 | 30 | 27 | 23 | 22 | 19 | 18 | 20 | 19 | 17 | 16 | 15 | 14 | 12 | 9  |   |    |   |
| 1.00       |    | 36                 | 32 | 28 | 26 | 23 | 22 | 33 | 30 | 27 | 25 | 22 | 21 | 23 | 22 | 19 | 19 | 17 | 16 | 14 | 11 |   |    |   |
| 1.25       |    | 40                 | 35 | 32 | 30 | 27 | 26 | 36 | 33 | 30 | 28 | 26 | 24 | 26 | 25 | 23 | 22 | 20 | 19 | 16 | 13 |   |    |   |
| 1.50       |    | 42                 | 37 | 35 | 32 | 30 | 28 | 39 | 35 | 33 | 30 | 28 | 27 | 28 | 26 | 25 | 24 | 21 | 21 | 18 | 15 |   |    |   |
| 2.00       |    | 46                 | 40 | 40 | 36 | 35 | 32 | 42 | 38 | 37 | 34 | 33 | 30 | 32 | 30 | 29 | 27 | 25 | 24 | 21 | 17 |   |    |   |
| 2.50       |    | 49                 | 42 | 43 | 38 | 39 | 35 | 45 | 39 | 40 | 36 | 36 | 33 | 34 | 32 | 31 | 29 | 27 | 26 | 23 | 19 |   |    |   |
| 3.00       |    | 50                 | 43 | 46 | 40 | 41 | 37 | 46 | 41 | 42 | 38 | 39 | 35 | 36 | 33 | 33 | 31 | 29 | 27 | 24 | 20 |   |    |   |
| 4.00       |    | 53                 | 45 | 49 | 42 | 45 | 40 | 49 | 42 | 45 | 40 | 42 | 38 | 39 | 35 | 36 | 33 | 31 | 29 | 26 | 22 |   |    |   |
| 5.00       |    | 54                 | 46 | 51 | 44 | 48 | 42 | 50 | 43 | 47 | 41 | 44 | 39 | 40 | 36 | 38 | 35 | 32 | 31 | 28 | 24 |   |    |   |
| 10.00      |    | 58                 | 48 | 56 | 47 | 54 | 46 | 53 | 46 | 51 | 44 | 50 | 43 | 44 | 39 | 42 | 39 | 36 | 34 | 31 | 27 |   |    |   |

