



■ 東芝照明器具配光データシート

名 称	電球形蛍光灯シャンデリア
形 名	BFC-6054ZEL

保守率	良	0.74
	中	0.70
	否	0.62



光源	名 称	ネオボールZ
	形 名	EFG25EL/20-ZJ
	光束	1370 lm × 6

効 率	F	19 %
	F	32 %
	F	51 %
	器具光束	4228 lm

最大取付間隔	
A-A	1.4 H
B-B	1.4 H

備考	
----	--

前 面	
反射面	

光度 (cd/1000lm)				天井	80			70			50			30			20	0
θ	φ	A-A	B-B	C-C	反射率 (%)	壁	70	50	30	70	50	30	50	30	30	10	10	0
0°		72				床	30	10	30	10	30	10	30	10	30	10	30	10
10°		72																
20°		73																
30°		72																
40°		65																
50°		58																
60°		52																
70°		45																
80°		31																
90°		25																
100°		30																
110°		37																
120°		37																
130°		34																
140°		29																
150°		25																
160°		22																
170°		22																
180°		21																
				照 明 率 (×0.01)														
				室指数	0.60	0.80	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00	10.00			
				0.60	27	25	20	19	15	15	25	23	19	18	15	14	16	15
				0.80	32	29	25	23	20	19	30	27	23	22	19	18	20	19
				1.00	36	32	28	26	23	22	33	30	27	25	22	21	23	22
				1.25	40	35	32	30	27	26	36	33	30	28	26	24	26	25
				1.50	42	37	35	32	30	28	39	35	33	30	28	27	28	26
				2.00	46	40	40	36	35	32	42	38	37	34	33	30	32	30
				2.50	49	42	43	38	39	35	45	39	40	36	36	33	34	32
				3.00	50	43	46	40	41	37	46	41	42	38	39	35	36	33
				4.00	53	45	49	42	45	40	49	42	45	40	42	38	39	35
				5.00	54	46	51	44	48	42	50	43	47	41	44	39	40	36
				10.00	58	48	56	47	54	46	53	46	51	44	50	43	44	39

