



東芝照明器具配光データシート

名 称		蛍光灯器具		保守率	良	0.73	θ			
形 名		FHR-41800-P H9			中	0.69			φ	
					否	0.61				
光 源	名称	蛍光ランプ		効 率	F		0 %	最大取付間隔	備考	
	形名	FHF32EX-N-H			F		82 %			
	光束	4950 lm × 1			F		82 %			
前 面		下面開放		器具 光束	4073 lm		A-A	1.3 H		
反射面		塗装（白）			B-B	1.3 H				

光度 (cd/1000lm)				反射率 (%)	天井				70				50				30				20				0
θ	φ	A-A	B-B		壁	70	50	30	70	50	30	70	50	30	70	50	30	70	50	30	70	50	30	70	
0°		301	301	301	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0
10°		291	298	299	室指数 照 明 率 (×0.01)																				
20°		281	284	286	0.60	53	49	41	39	34	33	51	48	41	39	34	33	39	38	33	33	33	32	29	27
30°		261	261	265	0.80	63	57	52	49	44	43	61	56	51	48	44	42	49	47	43	42	42	41	38	36
40°		222	230	233	1.00	69	62	58	54	51	48	67	61	57	53	50	48	55	52	49	47	48	46	43	41
50°		159	190	186	1.25	75	67	65	60	58	54	73	66	64	59	57	54	61	57	55	53	54	52	48	47
60°		71	144	122	1.50	80	70	70	63	63	58	77	69	68	63	62	58	65	61	60	57	58	56	53	51
70°		44	90	47	2.00	86	75	78	70	71	65	83	74	76	69	70	64	72	67	67	63	65	62	59	58
80°		24	32	24	2.50	90	78	83	73	76	69	87	76	80	72	75	68	76	70	72	67	69	66	63	62
90°		0	0	0	3.00	93	80	86	76	81	72	90	78	84	75	79	71	79	73	75	70	72	69	66	65
100°		0	0	0	4.00	96	82	91	79	86	76	93	81	88	78	84	75	83	76	80	74	76	73	70	69
110°		0	0	0	5.00	99	83	94	81	90	78	95	82	91	80	87	78	86	78	83	76	79	75	73	71
120°		0	0	0	10.00	103	86	101	85	98	83	99	85	97	84	95	83	91	82	89	81	84	79	78	76

