


東芝照明器具配光データシート

名 称	蛍光灯器具	保 守 率	良	0.73		θ	
	形 名		中	0.69			
			否	0.61			
光 源	名 称	FHF32EX-N-H	効 率	F 	0 %	最大取付間隔	ϕ
	形 名			F 	85 %		
	光 束			F 	85 %		
前 面	下面開放	反 射 面	器具 光束	2985 lm	A-A	1.3 H	備 考
	塗装 (白)					1.3 H	

光度 (cd/1000lm)				反射率 (%)	天井		80						70						50						30		20	0				
$\theta \backslash \phi$	A-A	B-B	C-C		壁		70			50			30			70			50			30			50		30		30		10	0
					床		30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10
				室指数	照 明 率 (×0.01)																											
0°				0.60	54	50	43	40	35	34	53	49	42	40	35	34	41	39	34	34	34	33	30	28								
10°				0.80	65	59	53	50	46	44	63	58	52	49	45	44	51	48	44	43	44	43	39	37								
20°				1.00	71	64	60	55	52	49	69	63	59	55	51	49	56	54	50	48	49	48	44	42								
30°				1.25	78	69	67	61	59	56	75	68	66	61	58	55	63	59	57	54	55	54	50	48								
40°				1.50	82	72	72	65	65	60	79	71	70	64	63	59	67	63	61	59	60	58	54	52								
50°				2.00	89	77	80	72	73	67	86	76	78	71	72	66	74	69	69	65	67	64	61	59								
60°				2.50	93	80	85	75	79	71	90	79	83	74	77	70	78	73	74	69	71	68	65	63								
70°				3.00	96	82	89	78	83	74	92	81	86	77	81	74	82	75	78	72	74	71	68	67								
80°				4.00	99	84	94	81	89	78	96	83	91	80	87	78	86	78	82	76	78	75	72	71								
90°				5.00	102	86	97	83	93	81	98	85	94	82	90	80	88	80	85	78	81	77	75	73								
100°				10.00	106	89	104	87	101	86	102	88	100	86	98	85	94	84	92	83	87	82	80	78								
110°																																
120°																																
130°																																
140°																																
150°																																
160°																																
170°																																
180°																																

