

東芝照明器具配光データシート



名 称	蛍光灯器具
形 名	FHR-42962K-PN9

光源	名 称	蛍光ランプ
	形 名	FHF32EX-N-H
	光束	3520 lm × 2

前 面	ルーバー (アルミ・G)
反射面	塗装 (白)

保守率	良	0.73
	中	0.69
	否	0.61

効 率	F 	0 %
	F 	72 %
	F 	72 %
	器具光束	5076 lm

θ	
	0°
ϕ	

最大取付間隔	
A-A	1.2 H
B-B	1.5 H

備考	
----	--

光度 (cd/1000lm)				反射率 (%)	天井	80						70						50						30		20	0											
$\theta \backslash \phi$	A-A	B-B	C-C			壁			70			50			30			70			50			30			50		30		30		10	0				
						床			30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0			
				室指数																							照 明 率 (×0.01)											
0°				0.60		50	46	40	38	35	33	48	45	40	38	34	33	39	37	34	33	33	33	33	30	29												
10°				0.80		59	54	50	47	45	43	58	53	50	47	44	42	48	46	43	42	43	42	39	38													
20°				1.00		65	58	56	52	50	48	63	57	55	51	50	47	53	50	48	47	47	46	44	42													
30°				1.25		70	62	62	57	56	53	68	61	61	56	56	52	59	55	54	52	53	51	49	47													
40°				1.50		73	65	66	60	61	56	71	64	65	59	60	56	62	58	58	55	56	54	52	51													
50°				2.00		79	69	73	65	68	62	76	68	71	64	66	61	68	63	64	60	62	60	57	56													
60°				2.50		82	70	76	67	72	65	79	69	74	67	70	64	71	65	67	63	65	62	60	59													
70°				3.00		84	72	79	69	75	67	81	71	77	68	73	66	73	67	70	65	67	64	62	61													
80°				4.00		86	73	82	71	79	69	83	72	80	70	77	69	75	69	73	68	70	66	65	63													
90°				5.00		88	74	84	72	81	71	85	73	82	72	79	70	77	70	75	69	71	68	66	65													
100°				10.00		91	76	89	75	87	74	87	75	86	74	84	73	80	72	79	72	74	70	69	68													
110°																																						
120°																																						
130°																																						
140°																																						
150°																																						
160°																																						
170°																																						
180°																																						

