



東芝照明器具配光データシート

名 称	蛍光灯埋込ダウンライト
形 名	FLD-2777N (V) -ELB

保守率	良	0.74
	中	0.70
	否	0.61



光源	名 称	コンパクト形蛍光ランプ
	形 名	FDL27EX-L
	光束	1550 lm × 1

効 率	F	0 %
	F	61 %
	F	61 %
	器具 光束	949 lm

最大取付間隔	
A-A	1.4 H
B-B	1.4 H

備考	
----	--

前 面	下面開放
反射面	銀色鏡面仕上げ

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	234		
10°	236		
20°	227		
30°	220		
40°	185		
50°	131		
60°	81		
70°	35		
80°	3		
90°	0		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反射率 (%)	天井	80						70						50						30		20	0
	壁	70		50		30		70		50		30		50		30		30		10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
室指数		照 明 率 (×0.01)																					
0.60		40	37	32	30	27	26	39	36	32	30	27	26	31	29	26	26	26	25	23	22		
0.80		48	44	40	38	35	33	47	43	40	37	35	33	38	36	34	33	33	33	30	29		
1.00		53	47	45	42	40	38	51	46	44	41	39	37	42	40	38	37	37	36	34	33		
1.25		57	51	50	46	45	42	56	50	49	45	44	42	47	44	43	41	42	41	38	37		
1.50		60	53	54	49	49	45	59	52	52	48	48	45	50	47	46	44	45	43	41	40		
2.00		65	57	59	53	55	50	63	56	58	53	54	50	55	51	52	49	50	48	46	45		
2.50		68	59	63	55	59	53	66	58	61	55	57	52	58	54	55	52	53	51	49	48		
3.00		70	60	65	57	62	55	68	59	64	57	60	54	60	55	57	54	55	53	51	50		
4.00		72	62	69	60	66	58	70	61	67	59	64	57	63	58	61	56	58	55	54	52		
5.00		74	62	71	61	68	59	71	62	69	60	66	59	65	59	63	58	60	57	55	54		
10.00		77	64	75	63	74	63	74	64	73	63	71	62	68	61	67	61	63	60	59	57		

