

東芝照明器具配光データシート



名 称	蛍光灯埋込ダウンライト
形 名	FLD-2777N (W))-ELB

光源	名 称	コンパクト形蛍光ランプ
	形 名	FDL27EX-L
	光束	1550 lm × 1

前 面	下面開放
反射面	白色

保守率	良	0.74
	中	0.70
	否	0.61

効 率	F	0 %
	F	65 %
	F	65 %
	器具 光束	1005 lm



最大取付間隔	
A-A	1.4 H
B-B	1.4 H

備考	
----	--

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	221		
10°	223		
20°	216		
30°	211		
40°	179		
50°	136		
60°	91		
70°	51		
80°	23		
90°	0		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反射率 (%)	天井	80						70						50						30		20	0
	壁	70		50		30		70		50		30		50		30		30		10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0	
室指数		照 明 率 (×0.01)																					
0.60		41	38	32	30	27	26	40	37	32	30	26	26	31	29	26	25	25	25	22	21		
0.80		49	45	40	38	34	33	48	44	40	37	34	33	38	36	33	32	33	32	29	28		
1.00		54	48	45	42	39	37	52	47	44	41	39	37	43	40	38	36	37	36	33	32		
1.25		59	52	51	46	45	42	57	51	50	46	44	42	47	45	43	41	42	40	38	36		
1.50		62	55	54	49	49	45	60	54	53	49	48	45	51	48	46	44	45	43	41	39		
2.00		68	59	61	54	55	51	65	58	59	54	54	50	56	52	52	49	50	49	46	45		
2.50		71	61	65	57	60	54	68	60	63	56	58	53	59	55	56	52	54	51	49	48		
3.00		73	62	67	59	63	56	70	61	66	58	62	56	62	57	59	55	56	54	52	50		
4.00		76	64	71	62	68	59	73	63	69	61	66	59	65	60	62	58	59	57	55	54		
5.00		77	65	74	63	70	61	75	64	71	63	68	61	67	61	65	60	61	58	57	55		
10.00		81	68	79	67	77	65	78	67	76	66	75	65	71	64	70	63	66	62	61	60		

