



東芝照明器具配光データシート

名 称	蛍光灯器具
形 名	FLD-2780NMR (W)-ELB

保守率	良	0.70
	中	0.66
	否	0.61



光源	名 称	コンパクト形蛍光ランプ
	形 名	FDL27EX-L
	光束	1550 lm × 1

効 率	F	0 %
	F	23 %
	F	23 %
	器具 光束	355 lm

最大取付間隔

A-A	1.1 H
B-B	1.1 H

備考

前 面	ガラス (クリアー)
反射面	上部：銀色鏡面, 下部：バツフル黒

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	110		
10°	117		
20°	104		
30°	83		
40°	67		
50°	46		
60°	25		
70°	7		
80°	3		
90°	0		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反射率 (%)	天井	80						70						50						30		20	0
	壁	70		50		30		70		50		30		50		30		30		10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
室指数		照 明 率 (×0.01)																					
0.60		16	14	13	12	11	11	15	14	13	12	11	11	12	12	11	10	11	10	9	9		
0.80		19	17	16	15	14	13	18	17	16	15	14	13	15	14	14	13	13	13	12	12		
1.00		20	18	17	16	16	15	20	18	17	16	15	15	16	16	15	14	15	14	13	13		
1.25		22	19	19	18	17	16	21	19	19	17	17	16	18	17	17	16	16	16	15	14		
1.50		23	20	20	18	19	17	22	20	20	18	18	17	19	18	18	17	17	17	16	15		
2.00		25	21	22	20	21	19	24	21	22	20	20	19	21	19	20	19	19	18	18	17		
2.50		25	22	24	21	22	20	25	22	23	21	22	20	22	20	21	19	20	19	18	18		
3.00		26	22	24	21	23	21	25	22	24	21	23	20	23	21	22	20	21	20	19	19		
4.00		27	23	26	22	25	22	26	23	25	22	24	21	23	21	23	21	22	21	20	20		
5.00		27	23	26	23	25	22	27	23	26	22	25	22	24	22	23	21	22	21	21	20		
10.00		29	24	28	24	27	23	28	24	27	23	26	23	25	23	25	23	23	22	22	21		

