




東芝照明器具配光データシート

名 称	蛍光灯器具
形 名	FLD-2781NMR (W)-ELA

保守率	良	0.70
	中	0.66
	否	0.61



光源	名称	コンパクト形蛍光ランプ
	形名	FDL27EX-L
	光束	1550 lm × 1

効率	F	0 %
	F	31 %
	F	31 %
	器具光束	484 lm

最大取付間隔	
A-A	1.2 H
B-B	1.2 H

備考	
----	--

前面	ガラス (クリアー)
反射面	上部：銀色鏡面，下部：パップル白

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	126		
10°	134		
20°	121		
30°	102		
40°	85		
50°	65		
60°	42		
70°	20		
80°	7		
90°	0		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反射率 (%)	天井	80						70						50						30		20	0
	壁	70		50		30		70		50		30		50		30		30		10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
室指数		照 明 率 (×0.01)																					
0.60		20	19	16	15	14	13	20	18	16	15	13	13	15	15	13	13	13	13	11	11		
0.80		24	22	20	19	17	17	24	22	20	19	17	17	19	18	17	16	17	16	15	14		
1.00		26	24	22	21	20	19	26	23	22	21	19	18	21	20	19	18	19	18	17	16		
1.25		29	26	25	23	22	21	28	25	24	23	22	21	23	22	21	20	21	20	19	18		
1.50		30	27	27	24	24	22	29	26	26	24	24	22	25	23	23	22	22	22	20	20		
2.00		33	28	30	26	27	25	32	28	29	26	27	25	28	26	26	24	25	24	23	22		
2.50		34	29	31	28	29	26	33	29	31	27	29	26	29	27	27	26	26	25	24	24		
3.00		35	30	33	29	31	27	34	30	32	28	30	27	30	28	29	27	27	26	25	25		
4.00		36	31	35	30	33	29	35	31	33	29	32	29	32	29	30	28	29	28	27	26		
5.00		37	31	36	31	34	30	36	31	34	30	33	29	32	30	31	29	30	28	28	27		
10.00		39	32	38	32	37	32	37	32	37	32	36	31	34	31	34	31	32	30	29	29		

