

東芝照明器具配光データシート



名 称	蛍光灯器具
形 名	FHR-22711N-PN9

光源	名 称	コンパクト形蛍光ランプ
	形 名	FHP23EN
	光束	1770 lm × 2

前 面	バツフル (白)
反射面	塗装 (白)

保守率	良	0.69
	中	0.65
	否	0.61

効 率	F 	0 %
	F 	67 %
	F 	67 %
	器具光束	2390 lm



最大取付間隔	
A-A	1.3 H
B-B	1.2 H

備考	
----	--

光度 (cd/1000lm)			
θ \ ϕ	A-A	B-B	C-C
0°	273	273	273
10°	273	264	270
20°	267	243	256
30°	250	213	235
40°	200	173	199
50°	135	127	142
60°	89	81	82
70°	57	39	44
80°	16	13	15
90°	1	1	1
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井	80						70						50						30		20	0
	壁	70		50		30		70		50		30		50		30		30		10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
室指数		照 明 率 (×0.01)																					
0.60		45	41	35	34	30	29	43	40	35	33	30	29	34	33	29	28	29	28	25	24		
0.80		53	48	44	41	38	37	52	47	43	41	38	36	42	40	37	36	36	36	33	32		
1.00		58	52	49	45	43	41	56	51	48	45	43	41	46	44	42	40	41	40	37	36		
1.25		63	56	55	50	49	46	61	55	53	49	48	45	51	48	47	45	45	44	41	40		
1.50		66	58	58	53	53	49	64	57	57	52	52	49	55	51	50	48	49	47	44	43		
2.00		71	62	65	58	60	54	69	61	63	57	58	54	60	56	56	53	54	52	50	48		
2.50		74	64	69	61	64	57	72	63	67	60	62	57	63	58	60	56	57	55	53	52		
3.00		77	66	71	63	67	60	74	65	69	62	65	59	66	60	62	58	60	57	55	54		
4.00		79	68	75	65	72	63	77	67	73	64	70	62	69	63	66	61	63	60	58	57		
5.00		81	69	78	67	74	65	78	68	75	66	72	64	71	64	68	63	65	62	60	59		
10.00		85	71	83	70	81	69	82	70	80	69	78	68	75	67	73	67	69	65	64	63		

