

東芝照明器具配光データシート

非常灯

名 称	非常用蛍光灯併用形 (電池内蔵)
形 名	FTS-21848Y-EL15

保 守 率	0.70
光 束 換 算 係 数	1.00

光源	平常時	FL20SS・W/1 8 × 1
	非常時	FL20SS・W/1 8 × 1
光束	定 格	1 2 3 0 lm
	非常時	6 7 6 lm


前 面	
反 射 面	
塗 装 (白)	

θ	0°
	135° (C') 180° (A') 135° (C') 90° (B) 45° (C) 0° (A) 45° (C)
φ	
備 考	



配置表 (保守率、光束換算係数を含む)

取付高さ	2.1	2.4	2.6	3.0	3.5	4.0	4.5	5.0	6.0	7.0
単 体 配 置	A1	3.7	3.8	3.8	3.7	3.6	3.2	2.7	-	-
	A'1	3.7	3.8	3.8	3.7	3.6	3.2	2.7	-	-
	B1	2.7	2.8	2.8	2.9	2.8	2.5	2.1	-	-
	B'1	2.7	2.8	2.8	2.9	2.8	2.5	2.1	-	-
直 線 配 置 四 角 配 置	A2	9.2	9.4	9.6	10.0	10.2	10.2	10.0	9.0	7.2
	B2	7.2	7.4	7.6	7.8	8.0	8.2	8.2	8.0	6.0
	A4	8.9	9.3	9.5	9.9	10.2	10.2	10.0	9.0	7.2
	B4	7.0	7.3	7.5	7.7	8.0	8.2	8.2	8.0	6.0
壁 からの 最大取付距離	A0	2.6	2.6	2.6	2.7	2.6	2.5	2.6	2.8	2.7
	A'0	2.6	2.6	2.6	2.7	2.6	2.5	2.6	2.8	2.7
	B0	1.8	1.8	1.8	1.8	1.7	1.9	1.9	2.1	2.0
	B'0	1.8	1.8	1.8	1.8	1.7	1.9	1.9	2.1	2.0

配光曲線 (cd/1000lm)



— φ = 0°
 - - - 45°
 . . . 90°
 - . - 135°
 - . - 180°



東芝照明器具配光データシート


非常灯

名 称	非常用蛍光灯併用形 (電池内蔵)
形 名	FTS-21848Y-EL15

保 守 率
0.70
光 束 換 算 係 数
1.00

光源	平常時	FL20SS・W/1 8 × 1
	非常時	FL20SS・W/1 8 × 1
光束	定 格	1 2 3 0 lm
	非常時	6 7 6 lm

前 面
反 射 面
塗装 (白)

	θ	
	ϕ	
備考		

光度 (cd/1000lm)					
θ \ φ	0° (A)	45° (C)	90° (B)	135° (C')	180° (A')
0°	151	151	151	151	151
10°	151	150	147	150	151
20°	154	148	139	148	154
30°	156	142	125	142	156
40°	162	138	109	138	162
50°	160	129	85	129	160
60°	156	120	61	120	156
70°	146	106	36	106	146
80°	132	89	13	89	132
90°	122	77	1	77	122
100°	124	80	1	80	124
110°	125	72	1	72	125
120°	95	46	1	46	95
130°	60	22	1	22	60
140°	26	1	1	1	26
150°	1	1	1	1	1
160°	1	1	1	1	1
170°	1	1	1	1	1
180°	1	1	1	1	1

器具直下からの各方向への指定照度が得られる距離 (m) (保守率、光束換算係数を含む)																
照度 (lx) \ 取付け高さ (m)	2.1	2.4	2.6	3.0	3.5	4.0	4.5	5.0	6.0	7.0	8.0	10.0	12.0	14.0	16.0	
2	0°	3.7	3.8	3.8	3.8	3.7	3.6	3.2	2.7	-	-	-	-	-	-	
	45°	3.3	3.4	3.4	3.4	3.3	3.1	2.8	2.4	-	-	-	-	-	-	
	90°	2.7	2.8	2.8	2.9	2.8	2.7	2.5	2.1	-	-	-	-	-	-	
	135°	3.3	3.4	3.4	3.4	3.3	3.1	2.8	2.4	-	-	-	-	-	-	
	180°	3.7	3.8	3.8	3.8	3.7	3.6	3.2	2.7	-	-	-	-	-	-	
1	0°	4.9	5.0	5.1	5.3	5.3	5.4	5.4	5.3	4.9	3.9	2.4	-	-	-	
	45°	4.4	4.5	4.6	4.7	4.8	4.8	4.8	4.7	4.3	3.5	2.1	-	-	-	
	90°	3.4	3.6	3.7	3.8	4.0	4.0	4.1	4.0	3.7	3.0	1.8	-	-	-	
	135°	4.4	4.5	4.6	4.7	4.8	4.8	4.8	4.7	4.3	3.5	2.1	-	-	-	
	180°	4.9	5.0	5.1	5.3	5.3	5.4	5.4	5.3	4.9	3.9	2.4	-	-	-	
0.5	0°	6.3	6.5	6.7	6.9	7.2	7.4	7.5	7.6	7.6	7.5	7.1	5.5	-	-	
	45°	5.6	5.8	6.0	6.2	6.4	6.6	6.7	6.8	6.8	6.6	6.3	4.8	-	-	
	90°	4.2	4.5	4.6	4.9	5.1	5.3	5.5	5.6	5.7	5.7	5.4	4.2	-	-	
	135°	5.6	5.8	6.0	6.2	6.4	6.6	6.7	6.8	6.8	6.6	6.3	4.8	-	-	
	180°	6.3	6.5	6.7	6.9	7.2	7.4	7.5	7.6	7.6	7.5	7.1	5.5	-	-	

東芝照明器具配光データシート

非常灯

名 称	非常用蛍光灯併用形 (電池内蔵)	保守率	0.70	
形 名	FTS-21848Y-EL15	光束換算係数	1.00	
光源	平常時 FL20SS・W/1 8 × 1 非常時 FL20SS・W/1 8 × 1	前 面		
光 束	定 格 1 2 3 0 lm 非常時 6 7 6 lm	反射面		備 考
		塗装 (白)		

器具直下からの各方面への指定照度が得られる距離 (m) (保守率、光束換算係数を含む)

取付け高さ (m)	2.1	2.2	2.3	2.4	2.5	2.6	2.7	2.8	2.9	3.0	3.1	3.2	3.3	3.4	3.5	3.6
照度 (lx)	φ	0°	45°	90°	135°	180°	0°	45°	90°	135°	180°	0°	45°	90°	135°	180°
2		3.7	3.7	3.8	3.8	3.8	3.8	3.8	3.8	3.8	3.8	3.8	3.8	3.8	3.7	3.7
		3.3	3.3	3.4	3.4	3.4	3.4	3.4	3.4	3.4	3.4	3.4	3.4	3.4	3.3	3.3
		2.7	2.7	2.8	2.8	2.8	2.8	2.8	2.8	2.9	2.9	2.9	2.9	2.9	2.9	2.8
		3.3	3.3	3.4	3.4	3.4	3.4	3.4	3.4	3.4	3.4	3.4	3.4	3.4	3.3	3.3
		3.7	3.7	3.8	3.8	3.8	3.8	3.8	3.8	3.8	3.8	3.8	3.8	3.8	3.7	3.7
1		4.9	4.9	5.0	5.0	5.1	5.1	5.2	5.2	5.2	5.3	5.3	5.3	5.3	5.3	5.4
		4.4	4.4	4.5	4.5	4.6	4.6	4.6	4.7	4.7	4.7	4.7	4.7	4.8	4.8	4.8
		3.4	3.5	3.5	3.6	3.6	3.7	3.7	3.8	3.8	3.9	3.9	3.9	3.9	4.0	4.0
		4.4	4.4	4.5	4.5	4.6	4.6	4.6	4.7	4.7	4.7	4.7	4.8	4.8	4.8	4.8
		4.9	4.9	5.0	5.0	5.1	5.1	5.2	5.2	5.3	5.3	5.3	5.3	5.3	5.3	5.4
0.5		6.3	6.4	6.4	6.5	6.6	6.7	6.7	6.8	6.9	6.9	7.0	7.0	7.1	7.1	7.2
		5.6	5.7	5.8	5.8	5.9	6.0	6.0	6.1	6.1	6.2	6.2	6.3	6.3	6.4	6.5
		4.2	4.3	4.4	4.5	4.5	4.6	4.7	4.7	4.8	4.9	4.9	5.0	5.0	5.1	5.2
		5.6	5.7	5.8	5.8	5.9	6.0	6.0	6.1	6.1	6.2	6.2	6.3	6.3	6.4	6.5
		6.3	6.4	6.4	6.5	6.6	6.7	6.8	6.9	6.9	7.0	7.0	7.1	7.1	7.2	7.2

取付け高さ (m)	3.7	3.8	3.9	4.0	4.1	4.2	4.3	4.4	4.5	5.0	5.5	6.0	6.5	7.0	7.5	8.0
照度 (lx)	φ	0°	45°	90°	135°	180°	0°	45°	90°	135°	180°	0°	45°	90°	135°	180°
2		3.7	3.6	3.6	3.6	3.5	3.5	3.4	3.3	3.2	2.7	2.0	-	-	-	-
		3.3	3.2	3.2	3.1	3.1	3.0	3.0	2.9	2.8	2.4	1.8	-	-	-	-
		2.8	2.8	2.7	2.7	2.7	2.6	2.6	2.5	2.5	2.1	1.5	-	-	-	-
		3.3	3.2	3.2	3.1	3.1	3.0	3.0	2.9	2.8	2.4	1.8	-	-	-	-
		3.7	3.6	3.6	3.6	3.5	3.5	3.4	3.3	3.2	2.7	2.0	-	-	-	-
1		5.4	5.4	5.4	5.4	5.4	5.4	5.4	5.4	5.3	5.1	4.9	4.5	3.9	3.3	2.4
		4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.7	4.5	4.3	3.9	3.5	2.9	2.1
		4.0	4.0	4.0	4.0	4.0	4.1	4.1	4.1	4.1	4.0	3.9	3.7	3.4	3.0	2.6
		4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.7	4.5	4.3	3.9	3.5	2.9	2.1
		5.4	5.4	5.4	5.4	5.4	5.4	5.4	5.4	5.3	5.1	4.9	4.5	3.9	3.3	2.4
0.5		7.3	7.3	7.3	7.4	7.4	7.4	7.4	7.5	7.5	7.6	7.6	7.6	7.5	7.3	7.1
		6.5	6.6	6.6	6.6	6.6	6.6	6.7	6.7	6.7	6.8	6.8	6.8	6.7	6.6	6.3
		5.2	5.2	5.3	5.3	5.4	5.4	5.4	5.5	5.5	5.6	5.7	5.7	5.7	5.6	5.4
		6.5	6.6	6.6	6.6	6.6	6.6	6.7	6.7	6.7	6.8	6.8	6.8	6.7	6.6	6.3
		7.3	7.3	7.3	7.4	7.4	7.4	7.4	7.5	7.5	7.6	7.6	7.6	7.5	7.3	7.1

取付け高さ (m)	8.5	9.0	9.5	10.0	10.5	11.0	11.5	12.0	12.5	13.0	13.5	14.0	14.5	15.0	15.5	16.0
照度 (lx)	φ	0°	45°	90°	135°	180°	0°	45°	90°	135°	180°	0°	45°	90°	135°	180°
2		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
1		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
0.5		6.9	6.5	6.0	5.5	4.8	4.0	2.8	-	-	-	-	-	-	-	-
		6.0	5.7	5.3	4.8	4.3	3.6	2.5	-	-	-	-	-	-	-	-
		5.2	4.9	4.6	4.2	3.8	3.1	2.1	-	-	-	-	-	-	-	-
		6.0	5.7	5.3	4.8	4.3	3.6	2.5	-	-	-	-	-	-	-	-
		6.9	6.5	6.0	5.5	4.8	4.0	2.8	-	-	-	-	-	-	-	-