

東芝照明器具配光データシート

名 称		H I D埋込ダウンライト		保守率	良	0.72					
形 名		DD-05154			中	0.68					
					否	0.62					
光源	名 称	ネオセラ		効 率	F 	0 %			最大取付間隔		
	形 名	MT50CHE-VW			F 	65 %					
	光 束	5300 lm × 1			F 	65 %					
前 面				器具光束	3430 lm	A-A					0.5 H
反射面		銀色鏡面（ファセット）				B-B					0.5 H

光度 (cd/1000lm)				天井	80			70			50			30	20	0
0°	2041	25°	214	壁	70	50	30	70	50	30	50	30	30	10	0	
1°	2019	30°	152	床	30	10	30	10	30	10	30	10	30	10	10	0
2°	2010	35°	111	照 明 率 (×0.01)												
3°	1978	40°	68	室指数												
4°	1960	45°	33	0.60	57	53	51	49	48	46	57	52	51	49	48	46
5°	1909	50°	18	0.80	62	57	57	53	53	51	61	56	56	53	52	50
6°	1812	55°	11	1.00	66	60	61	56	57	54	65	59	60	56	56	54
7°	1736	60°	8	1.25	69	61	63	58	59	56	67	60	62	58	59	55
8°	1614	65°	7	1.50	71	62	65	59	62	57	69	62	64	59	61	57
9°	1515	70°	6	2.00	73	64	69	61	65	59	71	63	67	61	64	59
10°	1411	75°	6	2.50	75	65	71	63	68	61	73	64	69	62	66	61
11°	1309	80°	5	3.00	77	66	73	64	70	62	74	65	71	63	68	62
12°	1196	85°	3	4.00	79	67	76	66	73	64	76	66	74	65	71	64
13°	1108	90°	2	5.00	80	68	78	67	76	66	78	67	75	66	74	65
14°	1016			10.00	83	69	82	69	81	69	80	69	79	69	79	68
15°	902															
16°	800															
17°	690															
18°	586															
19°	501															
20°	433															

