



東芝照明器具配光データシート

名 称	蛍光灯器具
形 名	FHR-42713-D BM

保守率	良	0.73
	中	0.69
	否	0.61

	
θ	
	
ϕ	

光源	名 称	蛍光ランプ
	形 名	FHF32EX-N-H
	光束	4950 lm × 2

効 率	F	0 %
	F	72 %
	F	72 %
	器具 光束	7116 lm

最大取付間隔	
A-A	1.3 H
B-B	1.3 H

備考	
----	--

前 面	
反射面	塗装 (白)

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	271	270	271
10°	262	269	270
20°	255	256	260
30°	237	235	242
40°	192	206	211
50°	124	171	160
60°	61	130	94
70°	33	83	40
80°	13	31	15
90°	0	0	0
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井	80						70						50						30			20	0
	壁	70		50		30		70		50		30		50		30		30			10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0			
室指数		照 明 率 (×0.01)																						
0.60		47	43	37	35	31	30	45	42	36	34	30	30	35	34	30	29	29	29	26	25			
0.80		56	51	46	43	40	38	54	50	45	43	39	38	44	42	38	37	38	37	34	32			
1.00		61	55	51	48	45	43	59	54	50	47	44	42	49	46	43	42	42	41	38	37			
1.25		66	59	57	53	51	48	64	58	56	52	50	47	54	51	49	47	48	46	43	42			
1.50		70	62	62	56	55	51	68	61	60	55	54	51	58	54	53	50	51	49	47	45			
2.00		76	66	69	61	63	57	73	65	67	60	62	57	64	59	59	56	57	55	52	51			
2.50		79	68	73	64	67	61	76	67	71	63	66	60	67	62	63	59	61	58	56	54			
3.00		81	70	76	66	71	63	79	69	74	65	69	63	70	64	66	62	63	61	58	57			
4.00		84	72	80	69	76	67	81	71	77	68	74	66	73	67	70	65	67	64	62	60			
5.00		86	73	82	71	79	69	83	72	80	70	77	68	75	68	73	67	69	65	64	62			
10.00		90	75	88	74	86	73	87	74	85	73	83	72	79	72	78	71	73	69	68	67			

