

東芝照明器具配光データシート

名 称		蛍光灯器具		保守率	良	0.74	θ 0° φ		
形 名		FT-22305-GH 16			中	0.70			
					否	0.61			
光源	名称	蛍光ランプ		効 率	F 	18%		最大取付間隔	
	形名	FL20SS・W/18			F 	70%			
	光束	1230 lm × 2			F 	88%			
前 面				器具 光束	2180 lm	A-A	1.5 H		備考
反射面		塗装（白）					B-B		

光度 (cd/1000lm)				天井	80			70			50			30	20	0
$\theta \setminus \phi$	A-A	B-B	C-C	反射率 (%)	壁	70	50	30	70	50	30	50	30	30	10	0
0°	166	166	166	床	30	10	30	10	30	10	30	10	30	10	30	10
10°	161	166	166	室指数 照 明 率 (×0.01)												
20°	161	156	161	0.60	48	44	35	33	27	26	46	42	34	32	26	26
30°	161	141	154	0.80	58	52	44	42	36	34	55	50	42	40	34	33
40°	159	121	145	1.00	64	57	51	47	42	39	60	55	48	45	40	38
50°	153	97	133	1.25	71	63	58	53	48	45	66	60	55	51	46	44
60°	145	71	116	1.50	75	66	63	57	54	50	70	63	60	55	51	48
70°	144	43	103	2.00	82	72	71	64	63	57	77	68	68	61	60	55
80°	116	17	89	2.50	87	75	77	68	69	62	81	72	73	65	65	60
90°	81	0	55	3.00	90	77	81	71	73	66	85	74	77	68	70	63
100°	75	0	47	4.00	95	80	87	75	80	71	89	77	82	72	76	68
110°	65	0	44	5.00	97	82	91	78	85	74	91	79	86	75	81	71
120°	62	0	40	10.00	104	87	100	84	96	82	97	83	94	81	91	79
130°	55	0	27													
140°	36	0	14													
150°	17	0	0													
160°	2	0	0													
170°	0	0	0													
180°	0	0	0													

