

東芝照明器具配光データシート

名 称	蛍光灯器具
形 名	FT-22084NMK-GL15

保守率	良	0.74
	中	0.70
	否	0.61

θ	
	0°
ϕ	

光源	名 称	蛍光ランプ
	形 名	FL20S・W
	光束	1230 lm × 2

効 率	F	16%
	F	59%
	F	75%
	器具光束	1854 lm

最大取付間隔	
A-A	1.6 H
B-B	1.2 H
備考	

前 面	
反射面	ステンレスクリヤー塗装

光度 (cd/1000lm)			
$\theta \backslash \phi$	A-A	B-B	C-C
0°	137	137	137
10°	143	134	139
20°	150	126	140
30°	153	112	138
40°	146	94	129
50°	141	73	114
60°	141	50	101
70°	122	27	95
80°	85	9	62
90°	60	0	37
100°	83	0	51
110°	73	0	40
120°	57	0	30
130°	41	0	19
140°	23	0	7
150°	7	0	1
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井	80						70						50						30	20	0
	壁	70	50	30				70	50	30				50	30					30	10	0
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0
室指数	照 明 率 (×0.01)																					
0.60	41	38	30	29	23	23	39	36	29	27	23	22	26	25	21	21	19	19	15	13		
0.80	49	45	38	36	31	29	47	43	36	34	30	28	33	32	27	27	25	25	21	18		
1.00	55	49	43	40	36	34	51	47	41	39	34	33	38	36	32	31	29	29	24	22		
1.25	60	54	50	45	42	39	57	51	47	44	40	38	43	40	37	35	34	33	29	26		
1.50	64	56	54	49	46	43	60	54	51	47	44	41	46	43	41	39	37	36	32	28		
2.00	70	61	61	55	54	49	66	59	58	53	52	48	52	49	47	44	43	41	37	34		
2.50	74	64	66	58	59	53	70	61	62	56	56	51	56	52	51	48	46	45	40	37		
3.00	77	66	70	61	63	56	72	63	66	59	60	55	59	54	55	51	49	47	43	39		
4.00	81	69	75	64	69	61	76	66	70	62	66	59	63	58	59	55	53	51	47	43		
5.00	83	70	78	67	73	63	78	67	73	64	69	61	65	60	62	57	56	53	50	45		
10.00	88	74	85	72	82	70	83	71	80	69	78	67	71	64	69	63	62	58	55	51		

