

■ 東芝ランプ 配光データシート

名 称	ネオコンパクト フラット
形 名	EFF12EL/C9
光 束	500 lm × 1

保 守 率	良	0.74
	中	0.70
	否	0.62

--	--

効 率	F 	%
	F 	%
	F 	100 %
	器具 光束	500 lm

最大取付間隔	
A-A	1.3 H
B-B	1.3 H

備 考	
--------	--

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	238		
10°	234		
20°	222		
30°	205		
40°	180		
50°	152		
60°	122		
70°	93		
80°	64		
90°	43		
100°	38		
110°	36		
120°	29		
130°	25		
140°	24		
150°	21		
160°	19		
170°	20		
180°	0		

反射率 (%)	天井	80						70						50						30			20	0
	壁	70		50		30		70		50		30		50		30		30		10	0			
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0		
室指数		照 明 率 (×0.01)																						
0.60		57	52	43	40	34	33	54	50	41	39	33	32	38	36	31	30	29	28	24	21			
0.80		68	62	53	50	44	42	64	59	51	48	43	41	47	45	40	39	37	37	32	29			
1.00		75	67	60	56	51	48	71	64	58	54	49	47	53	50	46	44	43	42	36	33			
1.25		82	73	68	63	58	55	78	70	65	60	56	53	60	56	52	50	49	47	42	38			
1.50		87	77	74	67	64	60	82	73	70	65	62	58	64	60	57	54	53	51	46	42			
2.00		95	83	83	75	74	68	90	79	79	72	71	66	72	67	66	62	60	58	53	48			
2.50		100	86	89	79	81	73	94	83	85	76	77	71	77	71	71	66	65	62	57	53			
3.00		103	89	94	82	86	77	97	85	89	79	82	74	80	74	75	70	68	65	61	56			
4.00		108	92	100	87	93	82	102	88	95	84	89	80	85	78	81	75	73	70	65	60			
5.00		111	94	104	89	98	85	105	90	99	86	93	83	89	81	85	78	77	73	68	63			
10.00		117	98	113	96	110	93	111	95	107	93	104	90	96	87	93	85	84	79	75	70			

