

東芝照明器具配光データシート

名 称		蛍光灯器具		保守率	良	0.73				
形 名		FHR-22800-P H9			中	0.69				
					否	0.61				
光源	名称	蛍光ランプ								
	形名	FHF16EX-N-H								
	光束	2100 lm×2								
前 面				効 率	F 	0%	最大取付間隔			
反射面		塗装（白）			F 	80%			A-A	1.3H
					F 	80%			B-B	1.3H
					器具 光束	3356 lm				
				備 考						

光度 (cd/1000lm)				反射率 (%)	天井	80						70						50						30		20	0					
$\theta \backslash \phi$	A-A	B-B	C-C			壁	70			50			30			70			50			30			50		30		30		10	0
							70	50	30	70	50	30	70	50	30	50	30	30	10	0												
																					床	30	10	30	10	30	10	30	10	30	10	30
				室指数	照 明 率 (×0.01)																											
0°				0.60	49	46	38	36	31	30	48	44	37	36	31	30	36	35	30	29	30	29	26	24								
10°				0.80	59	54	48	45	40	39	58	53	47	44	40	39	45	43	39	38	38	37	34	32								
20°				1.00	65	59	54	50	46	44	63	57	53	49	46	44	51	48	45	43	44	42	39	37								
30°				1.25	72	64	61	56	53	50	69	62	60	55	52	50	57	54	51	49	50	48	44	43								
40°				1.50	76	67	66	60	58	54	73	65	64	59	57	54	61	57	55	53	54	52	48	47								
50°				2.00	82	72	74	66	67	61	80	70	72	65	66	61	68	63	63	60	61	59	55	54								
60°				2.50	86	74	79	69	72	65	83	73	76	69	71	65	72	67	68	63	65	62	59	58								
70°				3.00	89	76	82	72	77	68	86	75	80	71	75	68	76	69	71	66	68	65	63	61								
80°				4.00	93	79	87	76	83	73	90	78	85	75	80	72	80	73	76	71	73	69	67	65								
90°				5.00	95	80	90	78	86	75	92	79	88	77	84	74	82	75	79	73	75	72	69	68								
100°				10.00	100	83	97	82	95	81	96	82	94	81	92	80	88	79	86	78	81	77	75	73								
110°																																
120°																																
130°																																
140°																																
150°																																
160°																																
170°																																
180°																																

