

東芝照明器具配光データシート

名 称		蛍光灯器具		保守率	良	0.73			
形 名		FHR-22848-P H9			中	0.69			
					否	0.61			
光源	名称	蛍光ランプ		効 率	F 	0 %			最大取付間隔
	形名	FHF16EX-N-H			F 	83 %			
	光束	2100 lm × 2			F 	83 %			
前 面				器具 光束	3500 lm	備 考			
反射面		塗装（白）							
				A-A		1.3 H			
				B-B		1.3 H			

光度 (cd/1000lm)				反射率 (%)	天井 壁 床	80						70						50						30		20	0	
$\theta \backslash \phi$	A-A	B-B	C-C			70		50		30		70		50		30		50		30		30		10	0			
						30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0	
				室指数	照 明 率 (×0.01)																							
0°				0.60	51	47	39	37	32	31	50	46	38	37	32	31	37	36	31	30	30	30	26	25				
10°				0.80	62	56	49	46	42	40	60	55	49	46	41	40	47	45	40	39	39	39	35	33				
20°				1.00	68	61	56	52	48	45	66	59	55	51	47	45	53	50	46	44	45	44	40	38				
30°				1.25	74	66	63	58	55	52	72	65	62	57	54	51	59	56	53	51	51	50	46	44				
40°				1.50	79	69	68	62	60	56	76	68	67	61	59	56	63	59	57	55	56	54	50	48				
50°				2.00	86	75	77	69	70	64	83	73	75	68	68	63	71	66	66	62	63	61	57	56				
60°				2.50	90	77	82	72	75	68	87	76	80	71	74	67	75	70	70	66	68	65	62	60				
70°				3.00	93	80	86	75	80	71	90	78	83	74	78	71	79	72	74	69	71	68	65	63				
80°				4.00	97	82	91	79	86	76	93	81	88	78	84	75	83	76	80	73	76	72	70	68				
90°				5.00	99	84	94	81	90	78	96	83	91	80	87	78	86	78	83	76	78	75	72	71				
100°				10.00	104	87	101	86	99	84	100	86	98	85	96	83	92	83	90	82	85	80	78	77				
110°																												
120°																												
130°																												
140°																												
150°																												
160°																												
170°																												
180°																												

