

東芝照明器具配光データシート

名 称		蛍光灯器具		保 守 率	良	0.73		
形 名		FHT-22404-P H9			中	0.69		
					否	0.61		
光 源	名 称	蛍光ランプ						
	形 名	FHF16EX-N-H						
	光 束	2100 lm × 2						
前 面				効 率	F 	0 %	最大取付間隔	備 考
					F 	83 %		
					F 	83 %		
					器具 光束	3500 lm		
反射面		塗装（白）				A-A		1.3 H
						B-B		1.3 H

光度 (cd/1000lm)				反 射 率 (%)	天井		80						70						50						30		20	0						
$\theta \backslash \phi$	A-A	B-B	C-C		壁	70			50			30			70			50			30			50			30			30		10	0	
						床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	20	0
室指数					照 明 率 (×0.01)																													
0°	266	266	266	0.60	51	47	39	37	32	31	50	46	38	37	32	31	37	36	31	30	30	30	30	26	25									
10°	265	259	264	0.80	62	56	49	46	42	40	60	55	49	46	41	40	47	45	40	39	39	39	39	35	33									
20°	253	251	254	1.00	68	61	56	52	48	45	66	59	55	51	47	45	53	50	46	44	45	44	40	38										
30°	233	240	238	1.25	74	66	63	58	55	52	72	65	62	57	54	51	59	56	53	51	51	50	46	44										
40°	205	221	215	1.50	79	69	68	62	60	56	76	68	67	61	59	56	63	59	57	55	56	54	50	48										
50°	171	191	185	2.00	86	75	77	69	70	64	83	73	75	68	68	63	71	66	66	62	63	61	57	56										
60°	132	142	142	2.50	90	77	82	72	75	68	87	76	80	71	74	67	75	70	70	66	68	65	62	60										
70°	88	74	84	3.00	93	80	86	75	80	71	90	78	83	74	78	71	79	72	74	69	71	68	65	63										
80°	39	18	28	4.00	97	82	91	79	86	76	93	81	88	78	84	75	83	76	80	73	76	72	70	68										
90°	0	0	0	5.00	99	84	94	81	90	78	96	83	91	80	87	78	86	78	83	76	78	75	72	71										
100°	0	0	0	10.00	104	87	101	86	99	84	100	86	98	85	96	83	92	83	90	82	85	80	78	77										
110°	0	0	0																															
120°	0	0	0																															
130°	0	0	0																															
140°	0	0	0																															
150°	0	0	0																															
160°	0	0	0																															
170°	0	0	0																															
180°	0	0	0																															

