

東芝照明器具配光データシート

光源	名称	蛍光灯器具	保守率	良	0.73	θ	
	形名	FHR-34324NK-PR9		中	0.69		
				否	0.61		
	名称	コンパクト形蛍光ランプ	効率	F	0%	φ	
	形名	FHP32EN		F	60%		
	光束	2600 lm × 4		F	60%		
前面	ルーバー (白)	器具光束	6221 lm	最大取付間隔	A-A	1.2 H	備考
	塗装 (白)				B-B	1.1 H	

光度 (cd/1000lm)				反射率 (%)	天井	80						70						50						30		20	0					
$\theta \backslash \phi$	A-A	B-B	C-C		壁	70			50			30			70			50			30			50		30		30		10	0	
					床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0
室指数				照 明 率 (×0.01)																												
0°				41	38	33	31	28	27	40	37	33	31	28	27	32	30	28	27	27	27	24	23									
10°				48	44	41	38	36	34	47	43	40	38	35	34	39	37	35	34	34	33	31	30									
20°				52	47	45	42	40	38	51	46	44	41	39	38	43	40	39	37	38	37	34	33									
30°				57	50	50	45	45	42	55	49	49	45	44	42	47	44	43	41	42	40	38	37									
40°				59	52	53	48	48	45	58	51	52	47	47	44	50	46	46	44	44	43	41	40									
50°				64	56	58	52	54	49	62	55	57	51	53	49	54	50	51	48	49	47	45	44									
60°				66	57	61	54	57	52	64	56	60	54	56	51	57	52	54	50	52	50	48	47									
70°				68	59	64	56	60	54	66	58	62	55	59	53	59	54	56	52	54	51	50	49									
80°				71	60	67	58	64	56	68	59	65	57	62	56	61	56	59	55	56	54	52	51									
90°				72	61	69	59	66	58	70	60	67	59	65	57	63	57	61	56	58	55	54	53									
100°				75	63	73	62	72	61	72	62	71	61	70	60	66	60	65	59	61	58	57	56									
110°																																
120°																																
130°																																
140°																																
150°																																
160°																																
170°																																
180°																																

