

■ 東芝ランプ 配光データシート

名 称	電球形蛍光ランプ
形 名	EFR25EL/22
光 束	1200 lm × 1

保 守 率	良	0.74
	中	0.70
	否	0.62

効 率	F 	%
	F 	%
	F 	100 %
	器具 光束	1200 lm

最大取付間隔	
A-A	1.5 H
B-B	1.5 H

--	--

--	--

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	234		
10°	244		
20°	253		
30°	248		
40°	218		
50°	179		
60°	131		
70°	92		
80°	67		
90°	44		
100°	28		
110°	15		
120°	10		
130°	8		
140°	7		
150°	7		
160°	7		
170°	7		
180°	0		

反射率 (%)	天井	80						70						50						30		20		0
	壁	70						70						50						30		10		0
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0	0
室指数	照 明 率 (×0.01)																							
0.60	59	54	44	42	35	34	56	52	43	41	35	34	41	39	33	32	32	31	27	24				
0.80	70	64	56	52	46	44	67	62	54	51	45	43	51	48	43	42	41	40	35	33				
1.00	77	69	63	58	53	50	74	67	61	57	52	49	57	54	49	48	47	46	41	38				
1.25	85	76	71	65	61	57	81	73	69	64	60	56	64	61	57	54	54	52	47	44				
1.50	90	79	77	70	67	62	86	77	74	68	65	61	69	65	62	59	58	57	51	48				
2.00	98	85	87	77	77	71	94	83	83	75	75	69	77	72	71	67	66	64	59	56				
2.50	103	89	92	82	84	76	98	86	89	80	81	74	82	76	76	71	71	68	64	60				
3.00	107	91	97	85	89	80	102	89	93	83	86	78	86	79	80	75	75	72	67	64				
4.00	111	95	104	90	97	85	106	92	99	87	93	83	91	83	86	80	80	77	72	69				
5.00	114	97	107	92	101	88	109	94	103	90	97	86	94	86	90	83	84	79	76	72				
10.00	121	101	117	98	113	96	115	98	111	96	108	94	102	92	99	90	91	86	83	79				

