

■ 東芝ランプ 配光データシート

名 称	ネオボールZ
形 名	EFA10EL/8-R
光 束	485 lm × 1

保 守 率	良	0.74
	中	0.70
	否	0.62

--	--

効 率	F 	%
	F 	%
	F 	100 %
	器具 光束	485 lm

最大取付間隔	
A-A	1.8 H
B-B	1.8 H

--	--

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	68		
10°	71		
20°	74		
30°	77		
40°	83		
50°	86		
60°	90		
70°	93		
80°	94		
90°	93		
100°	88		
110°	85		
120°	78		
130°	68		
140°	59		
150°	49		
160°	41		
170°	27		
180°	0		

反射率 (%)	天井	80						70						50						30			20	0
	壁	70		50		30		70		50		30		50		30		30			10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0	
室指数		照 明 率 (×0.01)																						
0.60		49	45	35	33	26	25	45	41	32	30	24	23	26	25	20	20	16	16	11	7			
0.80		59	53	44	41	34	32	53	49	40	38	31	30	33	32	26	25	22	21	15	11			
1.00		65	59	50	46	40	38	59	54	46	43	37	35	38	36	31	30	26	25	19	13			
1.25		72	64	58	53	47	44	66	59	53	49	43	41	44	41	37	35	30	29	23	16			
1.50		77	68	63	57	52	49	70	63	58	53	48	45	48	45	41	39	33	32	25	19			
2.00		85	74	72	65	62	57	77	68	66	60	57	53	55	51	48	45	39	38	31	23			
2.50		90	78	78	69	69	62	82	72	71	64	63	58	59	55	53	49	43	41	34	26			
3.00		94	80	83	73	74	66	85	74	76	68	68	61	63	58	57	53	46	44	37	29			
4.00		99	84	90	78	82	72	90	78	82	72	75	67	67	62	62	58	51	49	41	33			
5.00		102	86	94	81	87	76	93	80	86	75	80	70	71	64	66	61	54	51	44	35			
10.00		109	91	104	88	100	85	99	85	95	82	91	79	79	71	76	69	62	58	52	42			

