

■ 東芝ランプ 配光データシート

名 称	LED電球
形 名	LEL-AW4N/2
光 束	340 lm × 1

保守率	良	1.00
	中	1.00
	否	1.00

--	--

効 率	F 	%
	F 	%
	F 	100 %
	器具 光束	340 lm

最大取付間隔	
A-A	1.4 H
B-B	1.4 H

備 考	
--------	--

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	239		
10°	237		
20°	230		
30°	218		
40°	200		
50°	176		
60°	146		
70°	112		
80°	80		
90°	53		
100°	34		
110°	23		
120°	15		
130°	10		
140°	3		
150°	1		
160°	0		
170°	0		
180°	0		

反射率 (%)	天井	80						70						50				30		20	0
	壁	70		50		30		70		50		30		50		30		30		10	0
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0
室指数		照 明 率 (×0.01)																			
0.60		57	52	41	39	32	31	54	50	40	38	31	30	37	36	29	29	28	27	22	20
0.80		67	61	51	48	41	40	64	59	50	47	40	39	46	44	38	37	36	35	30	27
1.00		77	69	61	56	50	47	73	66	59	55	49	46	55	52	46	44	44	42	37	34
1.25		84	75	69	63	58	54	80	72	66	61	56	53	62	58	53	51	50	49	43	40
1.50		90	79	76	69	65	60	85	76	73	67	63	59	67	63	59	56	56	54	48	45
2.00		98	86	86	76	75	69	93	83	82	74	73	67	76	70	68	64	64	61	56	52
2.50		104	89	92	81	83	75	98	87	88	79	80	73	81	75	74	70	69	66	61	57
3.00		108	92	97	85	89	79	102	89	93	83	85	77	85	79	79	74	74	70	65	61
4.00		113	96	104	90	96	85	107	93	99	88	93	83	91	83	86	79	79	75	71	67
5.00		116	98	109	93	102	89	110	95	104	91	98	87	95	86	90	83	83	79	75	70
10.00		123	103	119	100	114	97	117	100	113	98	109	95	103	93	100	91	92	87	83	79

