

東芝ランプ 配光データシート

名称	LED電球
形名	LEL-AW7L/D
光束	330 lm × 1

保守率	良	1.00
	中	1.00
	否	1.00

--	--

効率	F	%
	F	%
	F	100 %
	器具光束	330 lm

最大取付間隔	
A-A	1.3 H
B-B	1.3 H

備考	
----	--

光度 (cd/1000lm)		A-A	B-B	C-C
0°	φ	235		
10°		233		
20°		225		
30°		213		
40°		195		
50°		172		
60°		143		
70°		110		
80°		75		
90°		47		
100°		30		
110°		21		
120°		15		
130°		11		
140°		3		
150°		1		
160°		0		
170°		0		
180°		0		

反射率 (%)	天井				70				50				30		20		0			
	壁	70	50	30	70	50	30	50	30	50	30	30	10	10	10	0	0			
床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0	0		
室指数	照明率 (×0.01)																			
0.60	55	51	40	38	31	30	52	49	39	37	30	29	36	35	29	28	27	27	22	20
0.80	65	59	50	47	40	38	62	57	48	45	39	38	45	43	37	36	35	34	29	27
1.00	74	67	59	55	49	46	71	64	57	53	47	45	53	50	45	43	42	41	36	33
1.25	81	72	67	61	56	53	77	70	64	59	55	52	60	56	52	50	49	47	42	39
1.50	87	77	73	66	63	58	83	74	70	65	61	57	65	61	58	55	54	52	47	44
2.00	95	83	83	74	73	67	91	80	80	72	71	65	73	68	66	63	62	60	55	51
2.50	100	87	89	79	80	72	95	84	86	77	78	71	79	73	72	68	68	65	60	56
3.00	104	89	94	83	86	77	99	87	90	80	83	75	83	76	77	72	72	68	64	60
4.00	109	93	101	87	94	82	104	90	96	85	90	80	88	81	83	77	77	74	69	65
5.00	112	95	105	90	99	86	107	92	100	88	95	84	92	84	87	80	81	77	73	69
10.00	119	100	115	97	111	94	113	97	110	95	106	92	100	90	97	88	89	84	81	77

