

# 東芝照明器具配光データシート

名称	蛍光灯器具	保守率	良	0.66	θ	
	形名		FHD-52500M-PN8	中		
名称	蛍光ランプ		否	0.55		
形名	FHT57EX・H	効	F	0%		
光束	4300 lm × 2		F	53%		
前面		器具光束	F	53%	最大取付間隔	備考
	反射面		銀色鏡面仕上げ	4563 lm		
					B-B	1.3 H

光度 (cd/1000lm)				天井	80			70			50			30	20	0								
θ	φ	A-A	B-B		壁	70	50	30	70	50	30	50	30	30	10	0								
0°		171	171	床	30	10	30	10	30	10	30	10	30	10	30	0								
10°		196	176																					
20°		206	156																					
30°		183	148																					
40°		149	124																					
50°		133	93																					
60°		95	74																					
70°		50	36																					
80°		1	1																					
90°		1	1																					
100°		0	0																					
110°		0	0																					
120°		0	0																					
130°		0	0																					
140°		0	0																					
150°		0	0																					
160°		0	0																					
170°		0	0																					
180°		0	0																					
				室指数	照 明 率 (×0.01)																			
				0.60	34	31	26	25	22	21	33	30	26	25	22	21	25	24	21	21	21	20	18	17
				0.80	41	37	33	31	28	27	39	36	33	31	28	27	31	30	28	27	27	26	24	23
				1.00	44	40	37	35	33	31	43	39	37	34	32	31	35	33	31	30	31	30	27	26
				1.25	49	43	42	38	37	35	47	42	41	38	37	35	39	37	36	34	35	34	31	30
				1.50	51	45	45	41	41	38	50	44	44	40	40	37	42	39	39	37	37	36	34	33
				2.00	56	48	50	45	46	42	54	48	49	44	45	42	47	43	44	41	42	40	39	38
				2.50	58	50	53	47	50	45	56	49	52	47	49	44	49	46	47	44	45	43	41	40
				3.00	60	51	56	49	52	47	58	51	54	48	51	46	51	47	49	45	47	45	43	42
				4.00	62	53	59	51	56	49	60	52	57	50	55	49	54	49	52	48	49	47	46	45
				5.00	64	54	61	52	58	51	61	53	59	52	57	50	55	50	54	49	51	48	47	46
				10.00	66	56	65	55	64	54	64	55	63	54	61	53	59	53	58	52	54	51	50	49

