

東芝ランプ 配光データシート

名 称	ネオボールZ
形 名	EFA10EL/8-E 17-S
光 束	450 lm × 1

良	0.74
中	0.70
否	0.62

効 率	F 	%
	F 	%
	F 	100 %
	器具 光束	450 lm

最大取付間隔	
A-A	1.5 H
B-B	1.5 H

備 考	
--------	--

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-φ
0°	109		
10°	113		
20°	112		
30°	111		
40°	110		
50°	108		
60°	102		
70°	96		
80°	90		
90°	84		
100°	73		
110°	66		
120°	60		
130°	53		
140°	47		
150°	40		
160°	34		
170°	25		
180°	0		

反射率 (%)	天井	80						70						50						30		20	0
	壁	70		50		30		70		50		30		50		30		30		10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
室指数		照 明 率 (×0.01)																					
0.60		51	47	36	35	28	27	47	44	34	32	26	25	29	28	23	22	20	19	14	11		
0.80		61	55	46	43	36	35	56	52	43	40	34	33	37	35	30	29	26	25	20	15		
1.00		68	61	53	49	42	40	62	57	49	46	40	38	42	40	35	34	30	29	23	19		
1.25		75	67	60	55	50	47	69	62	56	52	47	44	48	45	41	39	35	34	28	22		
1.50		80	70	66	60	55	51	73	65	61	56	52	48	52	49	45	43	39	37	31	25		
2.00		88	76	75	67	65	59	81	71	70	63	61	56	60	55	53	50	45	43	37	30		
2.50		93	80	81	72	72	65	85	75	75	67	67	61	64	59	58	54	49	47	41	34		
3.00		96	83	86	75	77	69	89	77	79	71	72	65	68	62	62	58	53	50	44	37		
4.00		101	86	92	80	85	74	93	81	85	75	79	70	73	67	68	62	57	55	48	41		
5.00		105	88	97	83	90	78	96	83	89	78	83	74	76	69	71	66	61	58	51	44		
10.00		112	93	107	90	102	87	103	88	99	85	95	82	84	76	81	73	69	65	59	51		

