




# 東芝ランプ 配光データシート

名称	ネオボールZ
形名	EFD15EL/10-PDS
光束	740 lm × 1

保守率	良	0.74
	中	0.70
	否	0.62

--	--

効率	F 	%
	F 	%
	F 	100 %
	器具光束	740 lm

最大取付間隔	
A-A	2.0 H
B-B	2.0 H

備考	
----	--

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	○-○
0°	68		
10°	74		
20°	82		
30°	93		
40°	99		
50°	101		
60°	99		
70°	93		
80°	89		
90°	84		
100°	78		
110°	74		
120°	74		
130°	68		
140°	58		
150°	47		
160°	35		
170°	24		
180°	0		

反射率 (%)	天井 80						70						50						30		20		0	
	壁		70		50		30		70		50		30		50		30		30		10		0	
床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0	0
室指数	照明率 (×0.01)																							
0.60	50	46	35	33	26	25	45	42	32	31	24	24	27	26	21	20	17	17	12	8				
0.80	59	54	44	41	34	33	54	50	41	39	32	31	35	33	27	27	23	23	17	12				
1.00	66	59	51	47	41	39	60	55	47	44	38	36	40	38	32	31	27	27	21	15				
1.25	73	65	59	54	48	45	67	60	54	50	45	42	46	43	38	37	32	31	25	19				
1.50	78	69	64	58	54	50	71	64	59	54	50	47	50	47	43	40	36	34	28	22				
2.00	86	75	74	66	64	58	79	70	68	61	59	54	57	53	50	47	42	40	34	26				
2.50	91	79	80	70	70	63	83	73	73	66	65	59	61	57	55	52	46	44	37	30				
3.00	95	81	84	74	76	67	87	76	78	69	70	63	65	60	59	55	49	47	40	32				
4.00	100	85	91	79	83	73	91	79	84	74	77	69	70	64	65	60	54	51	45	36				
5.00	103	87	95	82	88	77	94	82	88	77	81	72	73	67	69	63	57	54	48	39				
10.00	110	92	106	89	101	86	101	87	97	84	93	81	81	73	78	71	65	61	55	46				

