

東芝ランプ 配光データシート

名称	LED電球
形名	LEL-AW8N
光束	810 lm × 1

保守率	良	1.00
	中	1.00
	否	1.00

--	--

効率	F 	%
	F 	%
	F 	100 %
	器具光束	810 lm

最大取付間隔	
A-A	1.3 H
B-B	1.3 H

備考	
----	--

光度 (cd/1000lm)		A-A	B-B	C-C	D-D
0°	φ	245			
10°		243			
20°		237			
30°		223			
40°		202			
50°		177			
60°		147			
70°		112			
80°		75			
90°		46			
100°		28			
110°		19			
120°		13			
130°		9			
140°		6			
150°		1			
160°		0			
170°		0			
180°		0			

反射率 (%)	天井	80						70						50						30		20		0	
	壁	70		50		30		70		50		30		50		30		30		10		0		0	
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10
室指数	照明率 (×0.01)																								
	0.60	56	52	41	39	32	31	54	50	40	38	31	30	37	36	30	29	28	28	23	20				
	0.80	67	61	51	48	41	40	64	59	50	47	40	39	47	44	38	37	37	36	30	28				
	1.00	76	68	60	56	50	47	72	66	58	55	49	46	55	52	46	45	44	43	37	34				
	1.25	83	74	69	63	58	54	79	72	66	61	56	53	62	58	53	51	51	49	44	40				
	1.50	89	79	75	68	65	60	85	76	72	66	63	59	67	63	59	56	56	54	49	45				
	2.00	98	85	85	76	75	69	93	82	82	74	73	67	76	70	68	64	64	62	57	53				
	2.50	103	89	92	81	83	74	98	86	88	79	80	73	81	75	74	70	70	67	62	58				
	3.00	107	92	97	85	88	79	102	89	93	83	85	77	85	78	79	74	74	71	66	62				
	4.00	112	95	103	89	96	84	106	92	99	87	92	83	91	83	86	79	80	76	71	68				
	5.00	115	97	108	92	101	88	109	95	103	90	97	86	94	86	90	83	83	79	75	71				
	10.00	122	102	118	99	114	97	116	99	112	97	109	95	102	93	100	91	92	87	83	80				

