

東芝照明器具配光データシート



名 称	蛍光灯器具
形 名	FHR-42436D-PRJ

光源	名 称	蛍光灯ランプ
	形 名	FHF32EX-N-PD
	光束	2685 lm × 2

前 面	カバー (透明)
反射面	塗装 (白)

保守率	良	0.78
	中	0.74
	否	0.69

効 率	F 	0 %
	F 	69 %
	F 	69 %
	器具光束	3703 lm

θ	
	ϕ
ϕ	

最大取付間隔		備考
A-A	1.4 H	
B-B	1.3 H	

光度 (cd/1000lm)			
θ \ ϕ	A-A	B-B	C-C
0°	241	241	241
10°	235	238	240
20°	231	226	230
30°	222	205	216
40°	199	176	194
50°	160	140	159
60°	107	97	111
70°	59	51	56
80°	9	12	11
90°	1	1	1
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井	80						70						50				30		20	0
	壁	70		50		30		70		50		30		50		30		30		10	0
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0
室指数		照 明 率 (×0.01)																			
0.60		44	40	34	32	28	27	42	39	33	32	28	27	32	31	27	27	27	26	23	22
0.80		52	48	43	40	36	35	51	47	42	40	36	35	41	39	35	34	35	34	31	30
1.00		57	52	48	45	42	40	56	51	47	44	41	39	45	43	40	39	39	38	35	34
1.25		63	56	54	50	48	45	61	55	53	49	47	44	51	48	46	44	44	43	40	39
1.50		66	58	58	53	52	48	64	57	57	52	51	48	54	51	50	47	48	46	44	42
2.00		72	63	65	58	59	54	70	62	63	57	58	54	60	56	56	53	54	52	49	48
2.50		75	65	69	61	64	58	73	64	67	60	63	57	64	59	60	56	58	55	53	51
3.00		78	67	72	63	68	60	75	66	70	62	66	60	66	61	63	59	60	58	55	54
4.00		81	69	76	66	72	64	78	68	74	65	71	63	70	64	67	62	64	61	59	58
5.00		83	70	79	68	76	66	80	69	76	67	73	65	72	65	69	64	66	63	61	60
10.00		86	72	84	71	82	70	83	71	81	70	80	69	76	69	75	68	70	67	65	64

