


東芝ランプ 配光データシート

名称	LED電球 ミニクリ プトン形
形名	LDA4N-E17
光束	320 lm × 1

保守率	良	1.00
	中	1.00
	否	1.00



効率	F	9%
	F	9%
	F	100%
	器具 光束	320 lm

最大取付間隔	
A-A	1.4 H
B-B	1.4 H

備考
データは初期の標準値です。

光度 (cd/1000lm)	
0°	260
30°	250
40°	226
50°	187
60°	141
70°	99
80°	67
90°	43
10°	259
20°	259

反射率 (%)	天井	80						70						50						30		20		0
	壁	70	50	30	70	50	30	50	30	50	30	50	30	30	10	0								
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0					
室指数	照明率 (×0.01)																							
0.60	58	54	43	41	34	32	56	52	42	40	33	32	39	38	32	31	30	30	25	22				
0.80	69	63	54	50	44	42	66	61	52	49	43	41	49	47	41	40	39	38	33	30				
1.00	78	70	63	58	53	50	75	68	61	57	51	49	57	54	49	47	47	46	40	37				
1.25	86	76	71	65	61	57	82	74	69	64	59	56	64	61	56	54	54	52	47	44				
1.50	92	81	78	71	68	63	88	78	75	69	66	62	70	66	62	59	59	57	52	49				
2.00	100	87	88	79	78	71	96	85	85	77	76	70	79	73	72	68	67	65	60	57				
2.50	105	91	94	83	86	77	101	88	91	82	83	76	84	78	78	73	73	70	65	62				
3.00	109	94	99	87	91	81	104	91	95	85	88	80	88	81	82	77	77	74	69	66				
4.00	114	97	106	92	99	87	109	95	102	90	95	85	94	86	89	82	83	79	74	71				
5.00	117	99	110	95	104	90	112	97	106	93	100	89	97	88	93	85	86	82	78	74				
10.00	124	104	120	101	116	98	118	101	114	99	111	97	105	95	102	93	94	89	86	82				

