

東芝ランプ 配光データシート

名称	ネオボール
形名	EFA10EL/7-E
光束	455 lm × 1

保守率	良	0.74
	中	0.70
	否	0.62

--	--

効率	F	%
	F	%
	F	100 %
	器具光束	455 lm

最大取付間隔	
A-A	1.7 H
B-B	1.7 H

備考	
----	--

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	87		
10°	87		
20°	91		
30°	93		
40°	98		
50°	98		
60°	98		
70°	96		
80°	94		
90°	88		
100°	83		
110°	75		
120°	67		
130°	59		
140°	49		
150°	41		
160°	32		
170°	22		
180°	0		

反射率 (%)	天井	80						70						50						30		20		0	
	壁	70		50		30		70		50		30		50		30		30		10		0			
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0	0
室指数	照明率 (×0.01)																								
0.60	50	46	35	33	26	25	46	42	33	31	25	24	28	27	21	21	18	17	13	9					
0.80	59	54	44	42	35	33	54	50	41	39	32	31	35	33	28	27	23	23	17	13					
1.00	66	59	51	47	41	39	60	55	47	44	38	36	40	38	33	32	28	27	21	16					
1.25	73	65	59	54	48	45	67	60	54	50	45	42	46	43	38	37	32	31	25	19					
1.50	78	69	64	58	53	50	71	64	59	54	50	47	50	47	43	41	36	35	28	22					
2.00	86	75	73	66	63	58	79	70	68	61	59	54	57	53	50	47	42	41	34	27					
2.50	91	78	79	70	70	63	83	73	73	65	65	59	61	57	55	52	46	44	38	30					
3.00	95	81	84	74	75	67	87	76	77	69	70	63	65	60	59	55	50	47	41	33					
4.00	100	85	91	79	83	73	91	79	83	74	76	68	70	64	65	60	54	52	45	37					
5.00	103	87	95	82	88	77	94	81	87	77	81	72	73	67	69	63	57	55	48	40					
10.00	110	92	105	89	101	86	101	87	97	84	93	81	81	73	78	71	65	62	56	47					

