

東芝照明器具配光データシート

名 称	LED電球搭載アーム式ベッド灯
形 名	LEDA-04002

光源	名称	LED電球
	形名	LEL-AW7L
	光束	330 lm × 1

前 面	
反射面	塗装 (白)

保守率	良	0.60
	中	0.55
	否	0.50

効 率	F 	9 %
	F 	50 %
	F 	59 %
	器具光束	195 lm

--	--

最大取付間隔	
A-A	1.3 H
B-B	1.3 H

備考	
----	--

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	216		
10°	215		
20°	215		
30°	189		
40°	132		
50°	81		
60°	50		
70°	32		
80°	22		
90°	16		
100°	16		
110°	14		
120°	13		
130°	14		
140°	14		
150°	15		
160°	16		
170°	11		
180°	0		

反射率 (%)	天井	80						70						50						30		20	0
	壁	70		50		30		70		50		30		50		30		30		10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
室指数		照 明 率 (×0.01)																					
0.60		37	34	28	27	24	23	35	32	28	26	23	22	26	25	22	21	21	21	18	17		
0.80		43	39	35	33	30	28	41	37	34	32	29	28	32	30	27	27	26	25	23	21		
1.00		48	43	40	37	35	33	46	42	39	36	34	32	36	34	32	31	30	30	27	25		
1.25		52	46	45	41	39	37	50	45	43	40	38	36	40	38	36	34	34	33	30	28		
1.50		55	49	48	44	43	40	53	47	46	43	42	39	43	40	39	37	37	36	33	31		
2.00		60	52	53	48	49	44	57	50	51	46	47	43	47	44	44	41	41	39	37	35		
2.50		62	54	57	50	52	47	59	52	54	49	50	46	50	46	47	44	43	42	39	37		
3.00		64	55	59	52	55	49	61	53	57	50	53	48	52	48	49	46	45	43	41	39		
4.00		67	57	63	54	59	52	63	55	60	53	57	51	54	50	52	48	48	46	43	41		
5.00		68	58	65	56	62	54	65	56	62	54	59	52	56	51	54	50	49	47	45	42		
10.00		71	60	69	58	68	57	68	58	66	57	64	56	60	54	58	53	53	50	48	45		

