

東芝照明器具配光データシート

名 称		蛍光灯器具		保守率	良	0.78		
形 名		FB2342NB			中	0.74		
					否	0.70		
光源	名称	蛍光ランプ		効 率	F 	21%	最大取付間隔	
	形名	FL20SSEXN18Z			F 	46%		
	光束	1550 lm × 1			F 	67%		
前 面		グローブ（乳白）		器具 光束	1030 lm	A-A	1.3H	備考
反射面						B-B	1.8H	

光度 (cd/1000lm)				反射率 (%)	天井	80			70			50		30	20	0
$\theta \setminus \phi$	A-A	B-B	C-C		壁	70	50	30	70	50	30	50	30	30	10	0
0°	80	80	80		床	30	10	30	10	30	10	30	10	30	10	0
10°	80	81	82		室指数	照 明 率 (×0.01)										
20°	78	91	85		0.60	34	31	24	23	18	18	32	29	23	22	17
30°	72	97	88		0.80	41	37	31	29	24	23	38	35	29	27	23
40°	63	101	89		1.00	46	41	36	33	29	27	42	38	33	31	27
50°	53	102	87		1.25	51	45	41	37	34	32	47	42	38	35	32
60°	42	99	82		1.50	54	47	44	40	37	35	50	44	42	38	35
70°	30	93	75		2.00	59	52	51	45	44	40	55	49	47	43	42
80°	17	86	66		2.50	62	54	55	48	49	44	58	51	51	46	46
90°	10	78	58		3.00	65	56	58	51	52	47	60	53	54	48	49
100°	10	73	54		4.00	68	58	62	54	57	50	63	55	58	51	54
110°	9	66	48		5.00	70	60	65	56	61	53	65	56	61	53	57
120°	9	57	40		10.00	75	63	72	61	69	59	70	60	67	58	64
130°	8	46	31													
140°	8	34	22													
150°	8	21	13													
160°	0	0	0													
170°	0	0	0													
180°	0	0	0													

