

東芝照明器具配光データシート

名 称	東芝LED照明器具
形 名	LEDH82012Y-LC

効 率	F 	2 %	保 守 率	良	0.63
	F 	98 %		中	0.60
	F 	100 %		否	0.56
	器具 光束	5100 lm	最大取付間隔		

前 面		A-A	1.4 H
反射面		B-B	1.4 H

備 考	
--------	--

光度 (cd/1000lm)				反 射 率 (%)	天井	80						70						50						30		20	0	
$\theta \backslash \phi$	A-A	B-B	C-C		壁	70			50			30			70			50			30			50	30	10	0	
					床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0
					室指数	固 有 照 明 率 (×0.01)																						
0°	301	301	301	0.60	59	54	44	42	35	34	57	53	43	41	35	34	42	40	34	33	33	32	28	26				
10°	300	301	301	0.80	70	64	55	52	46	44	68	62	54	51	45	43	52	49	44	43	43	42	37	35				
20°	296	296	296	1.00	80	72	65	60	55	52	77	70	64	59	54	52	61	58	53	51	51	50	45	43				
30°	284	284	284	1.25	87	78	74	67	64	60	84	76	72	66	63	59	68	64	61	58	59	57	52	50				
40°	257	260	257	1.50	93	82	81	73	71	66	90	80	78	72	70	65	74	70	67	64	65	63	58	56				
50°	216	218	216	2.00	102	89	91	81	82	75	98	87	88	80	80	74	83	77	77	72	74	71	66	64				
60°	160	160	158	2.50	107	92	97	86	89	80	103	90	94	84	87	79	89	82	83	78	79	76	72	70				
70°	96	97	94	3.00	111	95	102	89	95	84	106	93	99	88	92	83	93	85	88	82	83	80	76	74				
80°	36	36	36	4.00	115	98	108	94	102	90	111	96	105	92	99	89	98	90	94	87	89	85	82	79				
90°	3	3	3	5.00	118	100	112	96	107	93	114	98	108	95	104	92	101	92	98	90	92	88	85	83				
100°	2	2	2	10.00	124	104	121	102	118	100	119	102	117	101	114	99	109	98	106	97	100	94	92	90				
110°	2	2	2																									
120°	2	3	3																									
130°	3	2	3																									
140°	3	3	3																									
150°	3	3	3																									
160°	3	3	3																									
170°	3	3	3																									
180°	0	0	0																									

