

東芝照明器具配光データシート

名 称		白熱灯スポットライト		保守率	良	0.86		
形 名		IB30123 (S) C			中	0.81		
					否	0.77		
光源	名称	ミニクリプトンレフランプ		効 率	F 	1 %	最大取付間隔	
	形 名	KR100／110V4 5WR50			F 	48 %		
	光束	450 lm × 1			F 	49 %		
前 面		カバー（透明）		器具 光束			A-A	1.0H
反射面		塗装（白）					B-B	1.0H
							備考	

光度 (cd/1000lm)				反 射 率 (%)	天井	80						70						50						30		20	0	
$\theta \backslash \phi$	A-A	B-B	C-C		壁	70		50		30		70		50		30		50		30		30		10	0			
					床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0	
室指数					照 明 率 (×0.01)																							
0°	334				0.60	34	32	28	27	25	24	34	31	28	27	24	24	27	26	24	24	24	23	21	21			
10°	322				0.80	40	36	34	32	30	29	39	35	33	31	30	28	32	31	29	28	28	28	26	25			
20°	281				1.00	44	39	38	35	34	33	43	39	38	35	34	32	36	34	33	32	32	30	29				
30°	212				1.25	47	42	42	38	38	36	46	41	41	38	37	35	39	37	36	35	35	34	33	32			
40°	124				1.50	49	43	44	40	41	38	48	43	43	40	40	38	42	39	39	37	38	37	35	34			
50°	63				2.00	52	46	48	43	45	41	51	45	47	43	44	41	45	42	42	40	41	39	38	37			
60°	32				2.50	54	47	51	45	48	43	53	46	49	44	47	43	47	43	45	42	43	41	40	39			
70°	12				3.00	56	48	52	46	50	44	54	47	51	45	49	44	48	44	46	43	44	42	41	40			
80°	2				4.00	57	49	55	47	53	46	55	48	53	47	51	46	50	46	48	45	46	44	43	42			
90°	1				5.00	58	49	56	48	54	47	56	49	54	48	53	47	51	47	50	46	47	45	44	43			
100°	1				10.00	61	51	59	50	58	50	58	50	57	49	56	49	54	48	53	48	50	47	46	45			
110°	1																											
120°	1																											
130°	1																											
140°	1																											
150°	1																											
160°	1																											
170°	1																											
180°	0																											

