

東芝ランプ 配光データシート

名称	
形名	EFD25EN/20-PDS
光束	1390 lm × 1

保守率	良	0.74
	中	0.70
	否	0.62

--	--

効率	F	%
	F	%
	F	100 %
	器具光束	1390 lm

最大取付間隔	
A-A	2.2 H
B-B	2.2 H

備考	
----	--

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	61		
10°	66		
20°	77		
30°	88		
40°	95		
50°	98		
60°	97		
70°	92		
80°	87		
90°	84		
100°	81		
110°	78		
120°	76		
130°	71		
140°	62		
150°	48		
160°	35		
170°	22		
180°	0		

反射率 (%)	天井	80						70						50						30		20		0	
	壁	70		50		30		70		50		30		50		30		30		10		0			
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0	10	0		
室指数	照明率 (×0.01)																								
0.60	49	45	35	33	26	25	45	42	32	30	24	23	27	26	20	20	17	16	12	12	8				
0.80	59	54	44	41	34	33	54	49	40	38	32	30	34	32	27	26	22	22	16	16	12				
1.00	66	59	51	47	40	38	60	54	47	44	38	36	39	37	32	31	27	26	20	20	15				
1.25	73	65	58	53	48	45	66	60	54	50	44	42	45	42	38	36	31	30	24	24	18				
1.50	78	68	64	58	53	49	71	63	59	54	49	46	49	46	42	40	35	34	27	27	21				
2.00	86	75	73	65	63	58	78	69	67	61	58	54	56	52	49	47	41	39	33	33	25				
2.50	91	78	79	70	70	63	83	73	73	65	64	59	60	56	54	51	45	43	36	36	29				
3.00	95	81	84	74	75	67	86	75	77	69	69	63	64	59	58	54	48	46	39	39	31				
4.00	100	85	91	78	83	73	91	79	83	73	76	68	69	63	64	59	53	50	44	44	35				
5.00	103	87	95	81	88	76	94	81	87	76	81	72	72	66	68	62	56	53	46	46	38				
10.00	110	92	105	89	101	85	100	86	96	83	92	80	80	72	77	70	64	60	54	54	44				

