

東芝照明器具配光データシート

名 称	LED照明器具
形 名	LEDB-20902L-LS1

効 率	F $\bigwedge$	18 %
	F $\bigcup$	82 %
	F $\bigcirc$	100 %
	器具 光束	405 lm

保 守 率	良	0.67
	中	0.63
	否	0.60

前 面	カバー（乳白）
反射面	

最大取付間隔	
A-A	1.23 H
B-B	1.37 H

備考

光度 (cd/1000lm)				反射率 (%)	天井 壁 床	80						70						50						30		20	0						
$\theta \backslash \phi$	A-A	B-B	C-C			70			50			30			70			50			30			50		30		30		10	0		
						30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0
室指数					固有照明率 (×0.01)																												
0.60					57	52	42	40	34	33	54	50	41	39	33	32	38	36	31	30	29	29	24	21									
0.80					68	62	53	50	44	42	65	59	51	48	43	41	48	45	40	39	38	37	32	29									
1.00					75	67	61	56	51	48	71	65	58	54	49	47	54	51	46	44	43	42	37	33									
1.25					83	73	69	63	59	55	78	70	66	61	57	54	60	57	53	51	49	48	42	39									
1.50					88	77	74	67	65	60	83	74	71	65	62	58	65	61	58	55	54	52	46	43									
2.00					96	83	84	75	75	68	90	80	80	73	72	66	73	68	66	62	61	59	54	49									
2.50					100	87	90	79	81	73	95	83	86	77	78	71	78	72	72	67	66	63	58	54									
3.00					104	89	95	83	87	77	98	86	90	80	83	75	81	75	76	71	69	66	61	57									
4.00					109	93	101	87	94	83	103	89	96	85	90	80	87	79	82	76	75	71	66	62									
5.00					112	95	105	90	99	86	106	91	100	87	94	84	90	82	86	79	78	74	69	65									
10.00					118	99	114	96	111	94	112	96	108	93	105	91	97	88	95	86	85	81	77	72									

